

**CITY OF
PEACHTREE CORNERS
PROPERTY
MAINTENANCE
CODE**



Adopted November 27, 2012

PROPERTY MAINTENANCE CODE SUMMARY

- **Burned Structures(Sec. 313)**: Damaged portions must be removed within 30 days. If repairs are possible, they must commence within 60 days and completed within 120 days. If the repairs are not possible, structures must be removed within 60 days.
- **Enforcement(104)**: The Community Development Department enforces the Property Maintenance Code and may call on personnel from other agencies such as police officers to assist in code enforcement.
- **Exterior Building Maintenance(Sec. 304)**: Maintenance is required of all exterior surfaces and building components including walls, roof, doors, windows, and stairways.
- **Grass and Weeds (Sec. 302.4)**: Over 12 inches prohibited.
- **Hazardous Trees(Sec. 311)**: Required to be removed.
- **Inactive Construction Sites(309)**: Property must be stabilized and all construction materials removed off sites where no construction has taken place in at least one year.
- **Junk Cars (Inoperable Vehicles) (Sec. 302.8A)**: Prohibited except when stored in an enclosed space or when located within a permitted zoning district.
- **Location of Parked Vehicles (Sec. 302.8B)**: All vehicles must be parked on a paved surface.
- **Open or Outdoor Storage(Sec. 310)**: Outdoor storage of appliances, building materials, rubbish, garbage, equipment, materials, merchandise and similar items is prohibited to be located on property for more than 24 hours except in permitted zoning districts, or for authorized sale of harvested products items such as Christmas trees and pumpkins, or firewood stacked in side or rear yards of residential property for the occupant's use.
- **Penalties(Sec. 106.4)**: Minimum fine of \$250; maximum fine of \$1000 and / or up to 60 days in jail.
- **Registered Agents(Sec. 312)**: an agent must be designated for every multi-family, commercial, office, and industrial property and the agent's, name, address, and phone number must be on file with the Community Development Department and updated once a year or prior to issuance of Certificate of Occupancy or Occupation Tax Certificate (business license).
- **Swimming Pools and Spas(Sec. 303.1)**: Must be maintained clean, free of algae and mosquitoes, and in good repair.
- **Tree Stumps and Tree Debris(Sec. 311.1, 311.2)**: Stumps over 12 inches above ground level and tree debris must be removed no more than 14 days after the tree has been cut.
- **Vacant Buildings(Sec. 301.3)**: Must be secured and kept in good repair, free of holes and infestation.

- **Walls and Fences (Sec. 304.6)**: Maintenance in sound condition required.

TABLE OF CONTENTS

<p>CHAPTER 1 ADMINISTRATION.....1</p> <p>Section</p> <p>101 General1</p> <p>102 Applicability1</p> <p>103 The Community Development Department.....2</p> <p>104 Duties and Powers of the Code Official.....2</p> <p>105 Approval.....2</p> <p>106 Violations3</p> <p>107 Notices and Orders3</p> <p>108 Unsafe Structures and Equipment.....4</p> <p>109 Emergency Measures4</p> <p>110 Demolition5</p> <p>111 Appeals5</p> <p>CHAPTER 2 DEFINITIONS6</p> <p>Section</p> <p>201 General6</p> <p>202 General Definitions6</p> <p>CHAPTER 3 GENERAL REQUIREMENTS8</p> <p>Section</p> <p>301 General8</p> <p>302 Exterior Property Areas8</p> <p>303 Swimming Pools, Spas and Hot Tubs9</p> <p>304 Exterior Structure9</p> <p>305 Interior Structure 10</p> <p>306 Handrails and Guardrail..... 10</p> <p>307 Rubbish and Garbage..... 11</p> <p>308 Extermination..... 11</p> <p>309 Inactive Construction Site... 11</p> <p>310 Open or Outdoor Storage.....12</p> <p>311 Trees.....12</p> <p>312 Registered Agents.....12</p> <p>313 Burned Structures.....12</p>	<p>CHAPTER 4 LIGHT, VENTILATION AND OCCUPANCY LIMITATIONS 13</p> <p>Section</p> <p>401 General..... 13</p> <p>402 Light..... 13</p> <p>403 Ventilation..... 13</p> <p>404 Occupancy Limitations 14</p> <p>CHAPTER 5 PLUMBING FACILITIES AND FIXTURE REQUIREMENTS..... 16</p> <p>Section</p> <p>501 General..... 16</p> <p>502 Required Facilities..... 16</p> <p>503 Toilet Rooms 16</p> <p>504 Plumbing Systems and Fixtures..... 16</p> <p>505 Water System 17</p> <p>506 Sanitary Drainage System..... 17</p> <p>507 Storm Drainage 17</p> <p>CHAPTER 6 MECHANICAL AND ELECTRICAL REQUIREMENTS..... 18</p> <p>Section</p> <p>601 General..... 18</p> <p>602 Heating Facilities 18</p> <p>603 Mechanical Equipment 18</p> <p>604 Electrical Facilities..... 19</p> <p>605 Electrical Equipment..... 19</p> <p>606 Elevators, Escalators and Dumbwaiters 19</p> <p>CHAPTER 7 FIRE SAFETY REQUIREMENTS..... 20</p> <p>Section</p> <p>701 General.....20</p> <p>702 Means of Egress.....20</p> <p>703 Fire-Resistance Ratings20</p> <p>704 Fire Protection Systems20</p> <p>CHAPTER 8 REFERENCE STANDARDS..... 22</p> <p>INDEX..... 23</p>
--	---

CHAPTER 1

ADMINISTRATION

SECTION 101 GENERAL

101.1 Title. These regulations shall be known as the Property Maintenance Code of the City of Peachtree Corners hereinafter referred to as "this code."

101.2 Scope. The provisions of this code shall apply to all existing residential and nonresidential structures and all existing premises and constitute minimum requirements and standards for premises, structures, equipment and facilities for light, ventilation, space, heating, sanitation, protection from the elements, life safety, safety from fire and other hazards, and for safe and sanitary maintenance; the responsibility of owners, operators and occupants; the occupancy of existing structures and premises, and for administration, enforcement and penalties.

101.3 Intent. This code shall be construed to secure its expressed intent, which is to ensure public health, safety and welfare insofar as they are affected by the continued occupancy and maintenance of structures and premises. Existing structures and premises that do not comply with these provisions shall be altered or repaired to provide a minimum level of health and safety as required herein. Repairs, alterations, additions to and change of occupancy in existing buildings shall comply with the *Georgia State Minimum Standard Existing Building Code*.

101.4 Severability. If a section, subsection, sentence, clause or phrase of this code is, for any reason, held to be unconstitutional, such decision shall not affect the validity of the remaining portions of this code.

SECTION 102 APPLICABILITY

102.1 General. The provisions of this code shall apply to all matters affecting or relating to structures and premises, as set forth in Section 101. Where, in a specific case, different sections of this code specify different requirements, the most restrictive shall govern.

102.2 Maintenance. Equipment, systems, devices and safeguards required by this code or a previous regulation or code under which the structure or premises was constructed, altered or repaired shall be maintained in good working order. No owner, operator or occupant shall cause any service, facility, equipment or utility which is required under this section to be removed from or shut off from or discontinued for any

occupied dwelling, except for such temporary interruption as necessary while repairs or alterations are in progress. The requirements of this code are not intended to provide the basis for removal or abrogation of fire protection and safety systems and devices in existing structures. Except as otherwise specified herein, the owner or the owner's designated agent shall be responsible for the maintenance of buildings, structures and premises.

102.3 Application of other codes. Repairs, additions or alterations to a structure, or changes of occupancy, shall be done in accordance with the procedures and provisions of the *Georgia State Minimum Standard Existing Building Code*. Nothing in this code shall be construed to cancel, modify or set aside any provision of the city *Unified Development Code* and such other state and city codes and laws, rules and regulations that may be applicable, as determined by the code official.

102.4 Existing remedies. The provisions in this code shall not be construed to abolish or impair existing remedies of the jurisdiction or its officers or agencies relating to the removal or demolition of any structure which is dangerous, unsafe, and unsanitary.

102.5 Workmanship. Repairs, maintenance work, alterations or installations which are caused directly or indirectly by the enforcement of this code shall be executed and installed in a workmanlike manner and installed in accordance with the manufacturer's installation instructions.

102.6 Historic buildings. The provisions of this code shall not be mandatory for existing buildings or structures designated as historic buildings when such buildings or structures are judged by the code official to be safe and in the public interest of health, safety, and welfare.

102.7 Referenced codes and standards. The codes and standards referenced in this code shall be those that are listed in Chapter 8 and considered part of the requirements of this code to the prescribed extent of each such reference. Where differences occur between provisions of this code and the referenced standards, the provisions of this code shall apply.

Wherever in this code the word "International" appears referencing particular ICC codes, the word "International" shall be deleted and the words "Georgia State" shall be inserted in its place.

102.8 Requirements not covered by code. Requirements necessary for the strength, stability, or proper operation of an existing fixture, structure, or equipment, or for the public safety, health, and general welfare, not specifically covered by this code, shall be determined by the code official.

SECTION 103

COMMUNITY DEVELOPMENT DEPARTMENT

103.1 General. The Community Development Department is authorized to enforce this code and the Community Development Director, or her designee, is hereinafter referred to as the code official.

103.2 Deputies. The code official shall have the authority to appoint inspectors, other related technical officers, and personnel from other agencies to assist in implementing this code. Such officials shall also include police officers, fire department staff, and other public safety personnel.

103.4 Liability. The code official, officer, or employee charged with the enforcement of this code, while acting for the jurisdiction, shall not thereby be rendered liable personally, and is hereby relieved from all personal liability for any damage accruing to persons or property as a result of an act required or permitted in the discharge of official duties.

Any suit instituted against any officer or employee because of an act performed by that officer or employee in the lawful discharge of duties and under the provisions of this code shall be defended by the legal representative of the jurisdiction until the final termination of the proceedings. The code official or any subordinate shall not be liable for costs in an action, suit or proceeding that is instituted in pursuance of the provisions of this code; and any officer of the department, acting in good faith and without malice, shall be free from liability for acts performed under any of its provisions or by reason of any act or omission in the performance of official duties in connection therewith.

103.5 Fees. The fees for activities and services performed by the department in carrying out its responsibilities under this code shall be as established by the Community Development director.

SECTION 104

DUTIES AND POWERS OF THE CODE OFFICIAL

104.1 General. The code official shall enforce the provisions of this code.

104.2 Rule-making authority. The code official shall have authority as necessary in the interest of public health, safety, and general welfare, to adopt and promulgate rules and procedures; to interpret and implement the provisions of this code; to secure the intent thereof; and to designate requirements applicable because of local climatic or other conditions. Such rules shall not have the effect of waiving structural or fire performance requirements specifically provided for in this code, or of violating accepted engineering methods involving public safety.

104.3 Inspections. The code official shall make all of the required inspections, or may accept reports of inspection by approved agencies or individuals. All reports of such inspections shall be in writing and be certified by a responsible officer of such approved agency or by the responsible individual. The code official is authorized to engage such expert opinion as deemed necessary to report upon unusual technical issues that arise, subject to the approval of the appointing authority.

104.4 Right of entry. The code official is authorized to enter the structure, property or premises at reasonable times to inspect. If entry or access is refused or not obtained, the code official is authorized to pursue recourse as provided by law.

104.5 Identification. The code official shall carry proper identification when inspecting structures or premises in the performance of duties under this code.

104.6 Notices and orders. The code official shall issue all necessary notices or orders to ensure compliance with this code.

104.7 Department records. The code official shall keep official records of all business and activities of the department specified in the provisions of this code. Such records shall be retained in the official records as long as the building or structure to which such records relate remains in existence, unless otherwise provided for by other regulations.

104.8 Coordination of inspections. Whenever in the enforcement of this code, the responsibility of more than one agency or employee is involved, it shall be the duty of the code official to coordinate inspections and administrative orders as fully as practicable so that the owners and occupants of the structure shall not be subjected to visits by numerous inspectors or multiple or conflicting orders. Whenever an inspector from any agency or department observes an apparent or actual violation of some provision of some law, ordinance or code not within the inspector's authority to enforce, the inspector shall report the findings to the code official.

SECTION 105 APPROVAL

105.1 Modifications. Whenever there are practical difficulties involved in carrying out the provisions of this code, the code official shall have the authority to grant modifications for individual cases, provided the code official shall first find that special individual reason makes the strict letter of this code impractical and the modification is in compliance with the intent and purpose of this code and that such modification does not lessen health, life and fire safety requirements. The

details of action granting modifications shall be recorded and entered in the department files.

105.2 Alternative materials, methods and equipment. The provisions of this code are not intended to prevent the installation of any material or to prohibit any method of construction not specifically prescribed by this code, provided that any such alternative has been approved. An alternative material or method of construction shall be approved where the code official finds that the proposed design is satisfactory and complies with the intent of the provisions of this code, and that the material, method or work offered is, for the purpose intended, at least the equivalent of that prescribed in this code in quality, strength, effectiveness, fire resistance, durability, and safety.

105.3 Required testing. Whenever there is insufficient evidence of compliance with the provisions of this code, or evidence that a material or method does not conform to the requirements of this code, or in order to substantiate claims for alternative materials or methods, the code official shall have the authority to require tests to be made as evidence of compliance at no expense to the jurisdiction.

105.4 Material and equipment reuse. Materials, equipment, and devices shall not be reused unless such elements are in good repair or have been reconditioned and tested when necessary, placed in good and proper working condition, and approved.

SECTION 106 VIOLATIONS

106.1 Unlawful acts. It shall be unlawful for a person, firm, or corporation to be in conflict with, or in violation of, any of the provisions of this code.

106.2 Notice of violation. The code official shall serve a notice of violation or order in accordance with Section 107.

106.3 Prosecution of violation. Any person failing to comply with a notice of violation or order served in accordance with Section 107 shall be deemed guilty of a misdemeanor and the violation shall be deemed a strict liability offense. If the notice of violation is not complied with, the code official may institute the appropriate proceeding at law or in equity to restrain, correct, or abate such violation, or to require the removal or termination of the unlawful occupancy of the structure in violation of the provisions of this code or of the order or direction made pursuant thereto. In addition, the court shall have the power and authority to order the violation corrected in compliance with this code and the court may require payment of restitution or impose other punishment allowed by law. Any action taken by the court or the city against such premises shall be charged against the real estate upon which the structure is located and shall be a lien upon such real estate.

106.4 Violation penalties. Any person convicted by a court of competent jurisdiction of violating any provision of this code shall be guilty of violating a duly adopted ordinance of the city and shall be punished either by a fine of not less than \$250 per day and not to exceed \$1,000 per day, or by a sentence of imprisonment not to exceed 60 days in jail, or both. Each day that a violation continues after due notice has been served shall be deemed a separate offense.

106.5 Abatement of violation. The imposition of the penalties herein prescribed shall not preclude the legal officer of the jurisdiction from instituting appropriate action to restrain, correct or abate a violation, or to prevent illegal occupancy of a building, structure or premises, or to stop an illegal act, conduct, business, or utilization of the building, structure, or premises.

SECTION 107 NOTICES AND ORDERS

107.1 Notice to person responsible. Whenever the code official determines that there has been a violation of this code or has grounds to believe that a violation has occurred, notice shall be given in the manner prescribed in Sections 107.2 and 107.3 to the person responsible for the violation as specified in this code. Notices for condemnation procedures shall also comply with Section 108.3.

107.2 Form. Such notice prescribed in Section 107.1 shall be in accordance with all of the following:

1. Be in writing.
2. Include a description of the real estate sufficient for identification
3. Include a statement of the violation or violations and why the notice is being issued.
4. Include statement to contact the code official to receive orders for violation correction.

107.3 Method of service. Such notice shall be deemed to be properly served if a copy thereof is:

1. Delivered personally;
2. Sent by certified or first-class mail, or professional courier addressed to the last known address; or
3. If the notice is returned showing that the notice was not delivered, a copy thereof shall be posted in a conspicuous place in or about the structure affected by such notice.

107.4 Penalties. Penalties for noncompliance with orders and notices shall be as set forth in Section 106.4.

107.5 Transfer of ownership. It shall be unlawful for the owner of any dwelling unit or structure who has received a compliance order or upon whom a notice of violation has been served to sell, transfer, mortgage, lease or otherwise dispose of such dwelling unit or structure to another until the provisions

of the compliance order or notice of violation have been complied with.

107.6 Stop Work Order. A Stop Work Order (Cease and Desist Notice) shall be issued to those sites found in violation of working without required city permits or licenses or using a site in violation of city codes and ordinances.

SECTION 108 UNSAFE STRUCTURES AND EQUIPMENT

108.1 General. When a structure or equipment is found by the code official to be unsafe, or when a structure is found unfit for human occupancy, or is found unlawful, such structure may be condemned pursuant to the provisions of this code.

108.1.1 Unsafe structures. An unsafe structure is one that is found to be dangerous to the life, health, property or safety of the public or the occupants of the structure by not providing minimum safeguards to protect or warn occupants in the event of fire, or because such structure contains unsafe equipment or is so damaged, decayed, dilapidated, structurally unsafe or of such faulty construction or unstable foundation, that partial or complete collapse is possible.

108.1.2 Unsafe equipment. Unsafe equipment includes any boiler, heating equipment, elevator, moving stairway, electrical wiring or device, flammable liquid containers or other equipment on the premises or within the structure which is in such disrepair or unsafe condition that such equipment is a hazard to life, health, property or safety of the public or occupants of the premises or structure.

108.1.3 Structure unfit for human occupancy. A structure is unfit for human occupancy whenever the code official finds that such structure is unsafe, unlawful, or because of the degree to which the structure is in disrepair or lacks maintenance, is unsanitary, vermin or rat infested, contains filth and contamination, or lacks ventilation, illumination, sanitary, or heating facilities or other essential equipment required by this code, or because the location of the structure constitutes a hazard to the occupants of the structure or to the public.

108.1.4 Unlawful structure. An unlawful structure is one found in whole or in part to be occupied or used by more persons than permitted under this code, or was erected, altered, or occupied contrary to law.

108.2 Closing of vacant structures. If the structure is vacant and unfit for human habitation and occupancy, and is not in danger of structural collapse, the code official is authorized to

post a placard of condemnation on the premises and order the structure closed up so as not to be an attractive nuisance. Upon failure of the owner to close up the premises within the time specified in the order, the code official shall cause the premises to be closed and secured through any available public agency or by contract or arrangement by private persons and the cost thereof shall be charged against the real estate upon which the structure is located and shall be a lien upon such real estate and may be collected by any other legal resource.

108.3 Notice. Whenever the code official has condemned a structure or equipment under the provisions of this section, notice shall be posted in a conspicuous place in or about the structure affected by such notice and served on the owner or the person or persons responsible for the structure or equipment in accordance with Section 107.3. If the notice pertains to equipment, it shall also be placed on the condemned equipment. The notice shall be in the form prescribed in Section 107.2.

108.4 Placarding. Upon failure of the owner or person responsible to comply with the notice provisions within the time given, the code official shall post on the premises or on defective equipment a placard bearing the word "Condemned" and a statement of the penalties provided for occupying the premises, operating the equipment, or removing the placard.

108.4.1 Placard removal. The code official shall remove the condemnation placard whenever the defect or defects upon which the condemnation and placarding action were based have been eliminated. Any person who defaces or removes a condemnation placard without the approval of the code official shall be subject to the penalties provided by this code.

108.5 Prohibited occupancy. Any occupied structure condemned and placarded by the code official shall be vacated as ordered by the code official. Any person who shall occupy a placarded premise or shall operate placarded equipment, and any owner or any person responsible for the premises who shall let anyone occupy a placarded premises or operate placarded equipment shall be liable for the penalties provided by this code.

SECTION 109 EMERGENCY MEASURES

109.1 Imminent danger. When, in the opinion of the code official, there is imminent danger of failure or collapse of a building or structure which endangers life, or when any structure or part of a structure has fallen and life is endangered by the occupancy of the structure, or when there is actual or potential danger to the building occupants or those in the proximity of any structure because of explosives, explosive fumes or vapors, or the presence of toxic fumes, gases, or materials, or operation of defective or dangerous equipment,

the code official is hereby authorized and empowered to order and require the occupants to vacate the premises forthwith.

The code official shall cause to be posted at each entrance to such structure a notice reading as follows: "This Structure Is Unsafe and Its Occupancy Has Been Prohibited by the Code Official." It shall be unlawful for any person to enter such structure except for the purpose of securing the structure, making the required repairs, removing the hazardous condition or of demolishing the same.

109.2 Temporary safeguards. Notwithstanding other provisions of this code, whenever, in the opinion of the code official, there is imminent danger due to an unsafe condition, the code official shall order the necessary work to be done, including the boarding up of openings, to render such structure temporarily safe whether or not the legal procedure herein described has been instituted; and shall cause such other action to be taken as the code official deems necessary to meet such emergency.

109.3 Closing streets. When necessary for public safety, the code official shall temporarily close structures and close, or order the authority having jurisdiction to close, sidewalks, streets, public ways and places adjacent to unsafe structures, and prohibit the same from being utilized.

109.4 Emergency repairs. For the purposes of this section, the code official may employ the necessary labor and materials to perform the required work as expeditiously as possible.

109.5 Costs of emergency repairs. Costs incurred in the performance of emergency work may be paid by the city. The city attorney may institute appropriate action against the owner of the premises where the unsafe structure is or was located for the recovery of such costs.

109.6 Hearing. Any person ordered to take emergency measures shall comply with such order forthwith. Any affected person shall thereafter, upon petition directed to the appeals board, be afforded a hearing as described in this code.

SECTION 110 DEMOLITION

110.1 General. The code official shall order the owner of any premises upon which is located any structure, which in the code official's judgment is so old, dilapidated, or has become so out of repair as to be dangerous, unsafe, unsanitary, or otherwise unfit for human habitation, use, or occupancy and such that it is unreasonable to repair the structure, to demolish and remove such structure; or if such structure is capable of being made safe by repair, to repair and make safe and sanitary or to demolish and remove at the owner's option, or where there has been a cessation of normal construction of any structure for a period of more than one year (see inactive construction site).

110.2 Notices and orders. All notices and orders shall comply with Section 107.

110.3 Failure to comply. If the owner of a premises fails to comply with a demolition order within the time prescribed, the code official may cause the structure to be demolished and removed, either through an available public agency or by contract or arrangement with private persons, and the cost of such demolition and removal shall be charged against the real estate upon which the structure is located and shall be a lien upon such real estate.

110.4 Salvage materials. When any structure has been ordered demolished and removed, the city council or its designee shall have the right to sell the salvage and valuable materials at the highest price obtainable. The net proceeds of such sale, after deducting the expenses of such demolition and removal, shall be promptly remitted with a report of such sale or transaction, including the items of expense and the amounts deducted, for the person who is entitled thereto, subject to any order of a court. If such a surplus does not remain to be turned over, the report shall so state.

SECTION 111 APPEALS

111.1 Application for appeal. Any person directly affected by a decision of the code official or a notice or order issued under this code shall have the right to appeal to the city Zoning Board of Appeals, provided that a written application for appeal is filed within 20 days after the day the decision, notice or order was served. An application for appeal shall be based on a claim that the true intent of this code or the rules thereunder have been incorrectly interpreted, the provisions of this code do not fully apply, or the requirements of this code are adequately satisfied by other means.

111.2 Board decision. The board shall modify or reverse the decision of the code official only by a concurring vote of a majority of the total number of appointed board members.

111.2.1 Records and copies. The decision of the board shall be recorded. Copies shall be furnished to the appellant and to the code official.

111.2.2 Administration. The code official shall take immediate action in accordance with the decision of the board.

111.3 Court review. Any person, whether or not a previous party of the appeal, shall have the right to apply to the appropriate court for a writ of certiorari to correct errors of law. Application for review shall be made in the manner and time required by law following the filing of the decision in the office of the Community Development Director.

111.4 Stays of enforcement. Appeals of notice and orders (other than Imminent Danger notices) shall stay the enforcement of the notice and order until the appeal is heard by the Zoning Board of Appeals.

CHAPTER 2

DEFINITIONS

SECTION 201 GENERAL

201.1 Scope. Unless otherwise expressly stated, the following terms shall, for the purposes of this code, have the meanings shown in this chapter.

201.2 Interchangeability. Words stated in the present tense include the future; words stated in the masculine gender include the feminine and neuter; the singular number includes the plural and the plural, the singular.

201.3 Terms defined in other codes. Where terms are not defined in this code and are defined in the Georgia State Minimum Standard Building and Fire Codes, such terms shall have the meanings ascribed to them as in those codes.

201.4 Terms not defined. Where terms are not defined through the methods authorized by this section, such terms shall have ordinarily accepted meanings such as the context implies.

201.5 Parts. Whenever the words "dwelling unit," "dwelling," "premises," "building," "rooming house," "rooming unit," "housekeeping unit," "structure," or "story" are stated in this code, they shall be construed as though they were followed by the words "or any part thereof."

SECTION 202 GENERAL DEFINITIONS

APPROVED. Approved by the code official.

BASEMENT. That portion of a building which is partly or completely below grade.

BATHROOM. A room containing plumbing fixtures including a water closet, lavatory, and bathtub, or shower.

BEDROOM. Any room or space used or intended to be used for sleeping purposes.

CODE OFFICIAL. The Community Development Director or her designee.

CONDEMN. To adjudge unfit for occupancy or use.

DWELLING UNIT. A single unit providing complete, independent living facilities for one or more persons, including permanent provisions for living, sleeping, eating, cooking and sanitation.

EASEMENT. That portion of land or property reserved for present or future use by a person or agency other than the legal fee owner(s) of the property. The easement shall be permitted to be for use under, on or above a said lot or lots.

EXTERIOR PROPERTY. The open space on the premises and on adjoining property under the control of owners or operators of such premises.

EXTERMINATION. The control and elimination of insects, rats, or other pests by eliminating their harborage places; by removing or making inaccessible materials that serve as their food; by poison spraying, fumigating, trapping, or by any other approved pest elimination methods.

GARBAGE. The animal or vegetable waste resulting from the handling, preparation, cooking, and consumption of food.

GUARD. A building component or a system of building components located at or near the open sides of elevated walking surfaces that minimizes the possibility of a fall from the walking surface to a lower level.

HABITABLE SPACE. Space in a structure for living, sleeping, eating, or cooking. Bathrooms, toilet rooms, closets, halls, storage, or utility spaces, and similar areas are not considered habitable spaces.

HOUSEKEEPING UNIT. A room or group of rooms forming a single habitable space equipped and intended to be used for living, sleeping, cooking, and eating which does not contain, within such a unit, a toilet, lavatory, and bathtub or shower.

IMMINENT DANGER. A condition which could cause serious or life threatening injury or death at any time.

INACTIVE CONSTRUCTION SITE. A property under development that has had no construction in at least one year, or has a permit that has been expired for at least six months, or a property that has not passed an inspection in at least six months.

INFESTATION. The presence, within or contiguous to, a structure or premises of insects, rats, vermin, or other pests.

INOPERABLE MOTOR VEHICLE (JUNK CAR). A vehicle which can not be driven upon the public streets for reason including, but not limited to, being unlicensed, wrecked, abandoned, in a state of disrepair, or incapable of being moved under its own power.

LABELED. Devices, equipment, appliances, or materials to which has been affixed a label, seal, symbol, or other identifying mark of a nationally recognized testing laboratory, inspection agency, or other organization concerned with product evaluation that maintains periodic inspection of the production of the above labeled items and by whose label the manufacturer attests to compliance with applicable nationally recognized standards.

LET FOR OCCUPANCY OR LET. To permit, provide, or offer possession, or occupancy, of a dwelling, dwelling unit, rooming unit, building, premise, or structure, or any portion thereof, by a person who is or is not the legal owner of record, or not the owner with the owner's written permission, pursuant to a written or unwritten lease, agreement or license, or pursuant to a recorded or unrecorded agreement of contract for the sale of land.

MAINTENANCE. The act of keeping property, structures or vegetation in a proper condition so as to prevent their decline, failure or uncontrolled growth.

OCCUPANCY. The purpose for which a building or portion thereof is utilized or occupied.

OCCUPANT. Any individual living or sleeping in a building, or having possession of a space within a building.

OPENABLE AREA. That part of a window, skylight, or door which is available for unobstructed ventilation and which opens directly to the outdoors.

OPERATOR. Any person who has charge, care, or control of a structure, or premises, which is let or offered for occupancy.

OWNER. Any person, agent, operator, firm, or corporation having a legal or equitable interest in the property; or recorded in the official records of the state, county, or municipality as holding title to the property; or otherwise having control of the property, including the guardian of the estate of any such person, and the executor or administrator of the estate of such person if ordered to take possession of real property by a court.

PERSON. An individual, corporation, partnership, or any other group acting as a unit.

PREMISES. A lot, plot, or parcel of land, easement, or public way, including any structures thereon.

PUBLIC WAY. Any street, alley, or similar parcel of land essentially unobstructed from the ground to the sky, which is deeded, dedicated, or otherwise permanently appropriated to the public for public use.

ROOMING HOUSE. A building arranged or occupied for lodging, with or without meals, for compensation and not occupied as a one or two family dwelling.

ROOMING UNIT. Any room or group of rooms forming a single habitable unit, occupied or intended to be occupied, for sleeping, or living, but not for cooking purposes.

RUBBISH. Combustible and noncombustible waste materials, except garbage; the term shall include the residue from the burning of wood, coal, coke, and other combustible materials, paper, rags, cartons, boxes, wood, excelsior, rubber, leather, tree branches, yard trimmings, tin cans, metals, mineral matter, glass, crockery, and dust and other similar materials. (The term **TRASH** is used interchangeably with the term **RUBBISH**)

STRICT LIABILITY OFFENSE. An offense in which the prosecution in a legal proceeding is not required to prove criminal intent as a part of its case. It is enough to prove that the defendant either did an act which was prohibited, or failed to do an act which the defendant was legally required to do.

STRUCTURE. That which is built or constructed or a portion thereof.

TENANT. A person, corporation, partnership, or group, whether or not the legal owner of record, occupying a building or portion thereof as a unit.

TOILET ROOM. A room containing a water closet or urinal but not a bathtub or shower.

VENTILATION. The natural or mechanical process of supplying conditioned or unconditioned air to, or removing such air from, any space.

WEEDS. All grasses, annual plants, and rank vegetative growth including but not limited to kudzu, poison ivy, jimsonweed, burdock, ragweed, thistle, cocklebur, dandelion, plants of obnoxious odors, or other similar unsightly vegetative growths; however, this term shall not include cultivated flowers, fruits and vegetables, and gardens, trees or shrubs.

WORKMANLIKE. Executed in a skilled manner; e.g., generally plumb, level, square, in line, undamaged, and without marring adjacent work.

YARD. An open space on the same lot with a structure.

YARD TRIMMINGS. Vegetative materials resulting from property maintenance such as grass clippings, leaves, brush, and tree pruning along with discarded vegetative material such as Christmas Trees.

CHAPTER 3 GENERAL REQUIREMENTS

SECTION 301 GENERAL

301.1 Scope. The provisions of this chapter shall govern the minimum conditions and the responsibilities of persons for maintenance of structures, equipment, and exterior property.

301.2 Responsibility. The owner of the premises shall maintain the structures and exterior property in compliance with these requirements, except as otherwise provided for in this code. A person shall not occupy as owner-occupant or permit another person to occupy premises which are not in a sanitary and safe condition and which do not comply with the requirements of this chapter. Occupants of a dwelling unit, rooming unit, or housekeeping unit are responsible for keeping in a clean, sanitary, and safe condition that part of the dwelling unit, rooming unit, housekeeping unit, or premises which they occupy and control.

301.3 Vacant structures and land. All vacant structures and premises thereof or vacant land shall be maintained in a clean, safe, secure, and sanitary condition as provided herein so as not to cause a blighting problem or adversely affect the public health or safety.

SECTION 302 EXTERIOR PROPERTY AREAS

302.1 Sanitation. All exterior property and premises shall be maintained in a clean, safe, and sanitary condition. The occupant shall keep that part of the exterior property which such occupant occupies or controls in a clean and sanitary condition.

302.2 Grading and drainage. All premises shall be graded and maintained to prevent the erosion of soil and to prevent the accumulation of stagnant water thereon, or within any structure located thereon.

Exception: Approved retention areas and reservoirs.

302.3 Sidewalks and driveways. All sidewalks, walkways, stairs, driveways, parking spaces, and similar areas shall be kept in a proper state of repair, and maintained free from hazardous conditions.

302.4 Yards. All premises yards and exterior property shall be maintained free from weeds in excess of 12 inches in height. All noxious weeds shall be prohibited.

Weeds shall be defined as all grasses, annual plants, and rank vegetative growth including but not limited to kudzu, poison ivy, jimsonweed, burdock, ragweed, thistle, cocklebur, dandelion, plants of obnoxious odors, or other similar unsightly vegetative growths; however, this term shall not include

cultivated flowers, fruits and vegetables, and gardens, trees or shrubs.

. All trees, shrubs, or other vegetation on the premises that block visibility of oncoming traffic from driveways or road intersections, or that are a danger to the public, or that are in advanced stages of rot, decay, or dying, as determined by the city arborist, shall be moved or removed and disposed of by the premises owner in a manner approved by the city.

Upon failure of the owner or agent having charge of a property to cut and destroy weeds after service of a violation notice, they shall be subject to prosecution in accordance with Section 106.3 and as prescribed by the city.

Upon failure to comply with the notice of violation, any duly authorized employee of the city, volunteer group, or contractor hired by the city, shall be authorized to enter upon the property in violation and cut and destroy the weeds growing thereon, and the costs of such removal shall be paid by the owner or agent responsible for the property.

302.5 Rodent harborage. All structures and exterior property shall be kept free from rodent harborage and infestation. Where rodents are found, they shall be promptly exterminated by approved processes which will not be injurious to human health. After extermination, proper precautions shall be taken to eliminate rodent harborage and prevent reinfestation.

302.6 Exhaust vents. Pipes, ducts, conductors, fans, or blowers shall not discharge gases, steam, vapor, hot air, grease, smoke, odors, or other gaseous or particulate wastes directly upon abutting or adjacent public or private property or that of another tenant.

302.7 Accessory structures. All accessory structures, including garages, storage buildings, playhouses, barns, fences, and walls, shall be maintained structurally sound and in good repair.

302.8 Motor vehicles. (A) Except in areas allowed by the Zoning Code, no inoperative or unlicensed motor vehicle shall be parked, kept, or stored on any premises, and no vehicle shall at any time be in a state of major disassembly, disrepair, or in the process of being stripped or dismantled. Painting of vehicles is prohibited unless conducted inside an approved spray booth.

Exception: A vehicle of any type is permitted to undergo major overhaul, including body work, provided that such work is performed inside a structure or similarly enclosed area designed and approved for such purposes.

(B) All vehicles must be parked on a paved surface. (See Zoning Code Sec.1001.5)

302.9 Defacement of property. No person shall willfully or wantonly damage, mutilate, or deface any exterior surface of

any structure or building on any private or public property by placing thereon any marking, carving, or graffiti.

It shall be the responsibility of the owner to restore said surface to an approved state of maintenance and repair.

SECTION 303

SWIMMING POOLS, SPAS AND HOT TUBS

303.1 Swimming pools and similar structures. Swimming pools and similar structures, such as spas and hot tubs, shall be maintained in a clean and sanitary condition, free of algae and mosquitoes, and kept in good repair.

303.2 Enclosures. Private swimming pools, hot tubs and spas, containing water more than 24 inches in depth shall be surrounded by an effective barrier at least 60 inches in height above the finished ground level measured on the side of the barrier away from the pool.

Exception: When such pools are located on property abutting a lake, pond, creek or river, the barrier may be omitted along the water side, provided side barriers extend to the water's edge.

Gates and doors in such barriers shall be self-closing and self-latching. Where the self-latching device is less than 54 inches above the bottom of the gate, the release mechanism shall be located on the pool side of the gate. Self-closing and self-latching gates shall be maintained such that the gate will positively close and latch when released from an open position of 6 inches from the gatepost.

No existing pool enclosure shall be removed, replaced, or changed in a manner that reduces its effectiveness as a safety barrier.

SECTION 304

EXTERIOR STRUCTURE

304.1 General. The exterior of a structure shall be maintained in good repair, structurally sound, and sanitary so as not to pose a threat to the public health, safety, or welfare.

304.2 Protective treatment. All exterior surfaces, including but not limited to, doors, door and window frames, cornices, porches, trim, balconies, decks, and fences shall be maintained in good condition. Exterior wood surfaces, other than decay resistant woods, shall be protected from the elements and decay by painting, or other protective covering or treatment. Peeling, flaking, and chipped paint shall be eliminated and surfaces repainted. All siding and masonry joints as well as those between the building envelope and the perimeter of windows, doors, and skylights shall be maintained weather resistant and water tight. All metal surfaces subject to rust or corrosion shall be coated to inhibit such rust and corrosion and all surfaces with rust or corrosion shall be stabilized and coated to inhibit future rust and corrosion. Oxidation stains shall be removed from exterior surfaces. Surfaces designed for stabilization by oxidation are exempt from this requirement.

304.3 Premises identification. Buildings shall have approved address numbers placed in a position to be plainly legible and

visible from the street or road fronting the property. These numbers shall contrast with their background. Address numbers shall be Arabic numerals or alphabet letters. Numbers shall be a minimum of 4 inches (102 mm) high with a minimum stroke width of 0.5 inch (12.7 mm).

304.4 Structural members. All structural members shall be maintained free from deterioration and shall be capable of safely supporting the imposed dead and live loads.

304.5 Foundation walls. All foundation walls shall be maintained plumb and free from open cracks and breaks and shall be kept in such condition so as to prevent the entry of rodents and other pests.

304.6 Exterior walls and Fences. All exterior walls and fences shall be free from holes, breaks, and loose or rotting materials and maintained weatherproof and properly surface coated where required to prevent deterioration. All damaged or missing portions of a fence shall be replaced with comparable materials and shall be attached to the existing portion of fence. Fences shall not be externally braced in lieu of replacing or repairing structural members.

304.7 Roofs and drainage. The roof and flashings shall be sound, tight, and not have defects that admit rain. Roof drainage shall be adequate to prevent dampness or deterioration in the walls or interior portion of the structure. Roof drains, gutters and downspouts shall be maintained in good repair and free from obstructions. Roof water shall not be discharged in a manner that creates a public nuisance.

304.8 Decorative features. All cornices, belt courses, corbels, terra cotta trim, wall facings, and similar decorative features shall be maintained in good repair with proper anchorage and in a safe condition.

304.9 Overhang extensions. All overhang extensions including, but not limited to canopies, marquees, signs, metal awnings, fire escapes, standpipes, and exhaust ducts shall be maintained in good repair and be properly anchored so as to be kept in a sound condition. When required, all exposed surfaces of metal or wood shall be protected from the elements and against decay or rust by periodic application of weather coating materials, such as paint or similar surface treatment.

304.10 Stairways, decks, porches and balconies. Every exterior stairway, deck, porch, balcony, and all appurtenances attached thereto, shall be maintained structurally sound, in good repair, with proper anchorage and capable of supporting the imposed loads.

304.11 Chimneys and towers. All chimneys, cooling towers, smoke stacks, other towers, and similar appurtenances shall be maintained structurally safe and sound, and in good repair. All exposed surfaces of metal or wood shall be protected from the elements and against decay or rust by periodic application of weather coating materials, such as paint or similar surface treatment.

304.12 Handrails and guards. Every handrail and guard shall be firmly fastened in place and capable of supporting normally imposed loads and shall be maintained in good condition.

304.13 Window, skylight and door frames. Every window, skylight, door, and frame shall be kept in a sound condition, in good repair, and weather tight.

304.13.1 Glazing. All glazing materials shall be maintained free from cracks and holes.

304.13.2 Openable windows. Every window, other than a fixed window, shall be easily openable and capable of being held in position by window hardware.

304.14 Insect screens. During the period from 1 April through 30 September, every exterior door, window, and other outside opening required for ventilation of commercial buildings, food preparation areas, food service areas, or any areas where products to be included or utilized in food for human consumption are processed, manufactured, packaged, or stored, shall be supplied with approved tight fitting screens of not less than 16 mesh per inch and every swinging door shall have a self-closing device in good working condition.

Exception: This requirement does not apply to restaurant patio seating areas.

304.15 Doors. All exterior doors, garage doors, door assemblies, and hardware shall be maintained in good condition. Locks at all entrances to dwelling units, rooming units, and guestrooms shall tightly secure the door. Locks on means of egress doors shall be in accordance with Section 702.3. Garage doors shall be capable of being closed reasonably plumb, properly attached and free of rot or noticeable deterioration.

304.16 Basement hatchways. Every basement hatchway shall be maintained to prevent the entrance of rodents, rain, and surface drainage water.

304.17 Guards for basement windows. Every basement window that is openable shall be supplied with rodent shields, storm windows, or other approved protection against the entry of rodents.

304.18 Building security. Doors, windows, or hatchways for dwelling units, room units, or housekeeping units shall be provided with devices designed to provide security for the occupants and property within.

304.18.1 Doors. Doors providing access to a dwelling unit, rooming unit, or housekeeping unit that is rented, leased, or let shall be equipped with a deadbolt lock meeting specifications set forth herein. Such deadbolt locks shall be operated only by the turning of a knob, or a key, and shall have a lock throw of not less than 1-inch. For the purpose of this section, a sliding bolt shall not be considered an acceptable deadbolt lock. Such deadbolt locks shall be installed according to manufacturer's specifications and maintained in good working order. All deadbolt locks required by this section shall be designed and installed in such a manner so as to be operable inside of the dwelling unit, rooming unit, or housekeeping unit without the use of a key, tool, combination thereof, or any other special knowledge or effort.

304.18.2 Windows. Operable windows, located in whole or in part within 6 feet (1828 mm) above ground level or a walking surface below, that provide access to a dwelling unit, rooming unit or housekeeping unit that is rented, leased, or let shall be equipped with a window sash locking devices.

304.18.3 Basement hatchways. Basement hatchways that provide access to a dwelling unit, rooming unit, or housekeeping unit that is rented, leased, or let shall be equipped with devices that secure the units from unauthorized entry.

SECTION 305 INTERIOR STRUCTURE

305.1 General. The interior of a structure and equipment therein shall be maintained in good repair, structurally sound, and in a sanitary condition. Occupants shall keep that part of the structure which they occupy or control in a clean and sanitary condition. Every owner of a structure containing a rooming house, housekeeping units, a hotel, a dormitory, two or more dwelling units or two or more nonresidential occupancies, shall maintain, in a clean and sanitary condition, the shared or public areas of the structure and exterior property.

305.2 Structural members. All structural members shall be maintained structurally sound, and be capable of supporting the imposed loads.

305.3 Interior surfaces. All interior surfaces, including windows and doors, shall be maintained in good, clean and sanitary condition. Peeling, chipping, flaking, or abraded paint shall be repaired, removed, or covered. Cracked or loose plaster, decayed wood, and other defective surface conditions shall be corrected.

305.4 Stairs and walking surfaces. Every stair, ramp, landing, balcony, porch, deck or other walking surface shall be maintained in a safe and sound condition and in good repair.

305.5 Handrails and guards. Every handrail and guard shall be firmly fastened and capable of supporting normally imposed loads and shall be maintained in good condition.

305.6 Interior doors. Every interior door shall fit reasonably well within its frame and shall be capable of being opened and closed by being properly and securely attached to jambs, headers or tracks as intended by the manufacturer of the attachment hardware.

SECTION 306 HANDRAILS AND GUARDRAILS

306.1 General. Every exterior and interior flight of stairs having more than four risers shall have a handrail on one side of the stair and every open portion of a stair, landing, balcony or porch, deck, ramp or other walking surface which is more than 30 inches above the floor or grade below shall have guards.

Handrails shall not be less than 30 inches high or more than 38 inches high measured vertically above the nosing of the tread or above the finished floor of the landing or walking surfaces.

Guards shall not be less than 36 inches high in residential dwelling unit uses, or 42 inches high in other uses, above the floor of the landing, balcony, porch, deck, or ramp or other walking surface.

Exception: Guards shall not be required where exempted by the adopted building code.

SECTION 307 RUBBISH AND GARBAGE

307.1 Accumulation of rubbish or garbage. All exterior property and premises, and the interior of every structure, shall be free from any accumulation of rubbish or garbage.

307.2 Disposal of rubbish. Every occupant of a structure shall dispose of all rubbish in a clean and sanitary manner by placing such rubbish in approved containers.

307.2.1 Rubbish storage facilities. The owner of every occupied premise shall supply approved covered containers for rubbish, and the owner of the premises shall be responsible for the removal of rubbish.

307.2.2 Refrigerators. Refrigerators and similar equipment not in operation shall not be discarded, abandoned or stored on premises without first removing the doors.

307.3 Disposal of garbage. Every occupant of a structure shall dispose of garbage in a clean and sanitary manner by placing such garbage in an approved garbage disposal facility or approved garbage containers.

307.3.1 Garbage facilities. The owner of every dwelling shall supply one of the following: an approved mechanical food waste grinder in each dwelling unit; an approved incinerator unit in the structure available to the occupants in each dwelling unit; or an approved leakproof, covered, outside garbage container.

307.3.2 Containers. The operator of every establishment producing garbage shall provide, and at all times cause to be utilized, approved leakproof containers provided with close fitting covers for the storage of such materials until removed from the premises for disposal.

SECTION 308 EXTERMINATION

308.1 Infestation. All structures shall be kept free from insect and rodent infestation. All structures in which insects or rodents are found shall be promptly exterminated by approved processes that will not be injurious to human health. After extermination, proper precautions shall be taken to prevent reinfestation.

308.2 Owner. The owner of any structure shall be responsible for extermination within the structure prior to renting or leasing the structure.

308.3 Single occupant. The occupant of a one family dwelling or of a single tenant nonresidential structure shall be responsible for extermination on the premises.

308.4 Multiple occupancy. The owner of a structure containing two or more dwelling units, a multiple occupancy, a rooming house, or a nonresidential structure shall be responsible for extermination in the public or shared areas of the structure and exterior property. If infestation is caused by failure of an occupant to prevent such infestation in the area occupied, the occupant shall be responsible for extermination.

308.5 Occupant. The occupant of any structure shall be responsible for the continued rodent and pest free condition of the structure.

Exception: Where the infestations are caused by defects in the structure, the owner shall be responsible for extermination.

SECTION 309 INACTIVE CONSTRUCTION SITE

309.1 Construction Inactivity. Whenever a development property remains inactive for at least one year, the property shall no longer be considered a construction site and shall be subject to the mitigation requirements of 309.2.

309.2 Mitigation. Within 30 days of notification by the city, the responsible party associated with an inactive construction site shall do the following:

- a. Remove all construction materials, supplies, and equipment from the site; and
- b. Remove all storage containers, construction trailers and security trailers from the site; and
- c. Remove all signage except permitted 'For Sale' or comparable real estate sign; and
- d. Stabilize the soil on the site pursuant to best practices; and
- e. Remove silt fencing and tree protection fencing as directed by the code official; and
- f. Remove any standing water and eliminate ponding conditions on site; and
- g. Complete any required drainage improvements needed to prevent downstream impacts; and
- h. Remove or safeguard any hazards on the site; and
- i. Remove unsafe partial structures; and
- j. Re-vegetate and/or screen the site (using materials approved by the code official) along roadways; and
- k. Mow, weed, and trim existing vegetation on site such that grass does not exceed eight inches in height, weeds are removed, and shrubs and trees are free of dead limbs or growth.

1. Submit a letter to the code official identifying the plan for on-going site maintenance (including watering schedule for vegetation) until such time as the construction permit is re-activated.

309.3 Non-Compliance. If the responsible party associated with an inactive construction site does not comply with any or all of the mitigation requirements established in Sec. 309.2, then the city may perform the minimum work necessary for compliance. Costs incurred in the performance of such work may be paid by the city and the city may institute all legal remedies available against the property and/or property owner to recover such costs incurred including, but not limited to, the filing of liens.

310. Open or Outdoor Storage. The open or outdoor storage of appliances, building materials, rubbish, equipment, garbage, goods, glass, materials, merchandise, or similar items shall not be permitted, maintained or stored on any property for more than 24 hours, except as follows:

1. Property where outdoor storage is allowed by the Zoning Code; and
2. Seasonal harvested products such as Christmas trees, pumpkins, firewood in conjunction with an authorized sale; and
3. Cut wood neatly stacked in lengths not exceeding 3 ft. and located on residential property for the personal use of the occupant.

311. Trees. Dead or hazardous trees shall not be allowed and shall be removed from property where they pose a threat to people or adjacent property. A finding by a forester or arborist or indisputable direct observation shall constitute sufficient evidence that a tree is in danger of falling upon adjacent lots or public streets.

311.1 Tree Stumps. Except on active construction sites, tree stumps greater than 12 inches in height above ground level shall not be permitted or maintained on any premises for more than 14 days after the tree has been cut.

311.2 Tree Debris. Felled trees or tree limbs shall not be permitted or maintained on the ground on any premises

for more than 14 days except on active construction sites or where wood has been cut in lengths not exceeding three feet and neatly stacked in a side or rear yard of residential property for the occupant's use.

312. Registered Agents. Prior to the issuance of a Certificate of Occupancy for a multi-family development, commercial, office, or industrial property or during the first thirty days of each year, whichever occurs earlier, the owner and each Occupation Tax Certificate (business license) holder for each multi-family development, commercial, office, or industrial property must designate the name, local address, e-mail address, and 24-hour phone number of an agent for the property. The agent shall reside in Gwinnett County and shall be on 24-hour call, seven days a week, to accept notices of violation regarding any provision of this code. In addition, written notice to such agent shall be deemed delivered on the third business day following the mailing of such notice by first class mail to the agent at the address listed in the registration. The registration required shall be submitted to the Community Development Department and the information shall be confirmed annually at the time of Occupational Tax Certificate (business license) renewal. Changes to contact information must be made by the business or property owner in writing and are not effective until received by the Community Development Department.

313. Burned Structures. Whenever any building or structure is partially burned, the owner or responsible party, within thirty days after the scene investigation by the Fire Department and/or insurer of the property, shall remove from the premises all refuse, debris, and all charred and partially burned lumber and materials. If such building or structure is burned to such an extent that it cannot be repaired, then the owner or responsible party, within sixty days after the Fire Department and insurer have completed their investigation, shall remove the remaining portions of the building or structure from the property. If the building or structure is to be repaired, work shall begin within sixty days and shall be completed within one-hundred and twenty days after the Fire Department and insurer have completed their investigation.

CHAPTER 4

LIGHT, VENTILATION AND OCCUPANCY LIMITATIONS

SECTION 401 GENERAL

401.1 Scope. The provisions of this chapter shall govern the minimum conditions and standards for light, ventilation, and space for occupying a structure.

401.2 Responsibility. The owner of the structure shall provide and maintain light, ventilation, and space conditions in compliance with these requirements. A person shall not occupy as owner-occupant, or permit another person to occupy, any premises that do not comply with the requirements of this chapter.

401.3 Alternative devices. In lieu of the means for natural light and ventilation herein prescribed, artificial light or mechanical ventilation complying with the *Georgia State Minimum Standard Building Codes* shall be permitted.

SECTION 402 LIGHT

402.1 Habitable spaces. Every habitable space shall have at least one window of approved size facing directly to the outdoors or to a court. The minimum total glazed area for every habitable space shall be 8 percent of the floor area of such room. Wherever walls or other portions of a structure face a window of any room and such obstructions are located less than 3 feet (914 mm) from the window and extend to a level above that of the ceiling of the room, such window shall not be deemed to face directly to the outdoors, nor to a court, and shall not be included as contributing to the required minimum total window area for the room.

Exception: Where natural light for rooms or spaces without exterior glazing areas is provided through an adjoining room, the unobstructed opening to the adjoining room shall be at least 8 percent of the floor area of the interior room or space, but not less than 25 square feet (2.33 m²). The exterior glazing area shall be based on the total floor area being served.

402.2 Common halls and stairways. Every common hall and stairway in residential occupancies, other than in one and two family dwellings, shall be lighted at all times with at least a 60 watt standard incandescent light bulb for each 200 square feet (19m²) of floor area or equivalent illumination, provided that the spacing between lights shall not be greater than 30 feet (9144 mm). In other than residential occupancies, means of egress, including exterior means of egress stairways shall be

illuminated at all times the building space served by the means of egress is occupied with a minimum of 1 foot-candle (11 lux) at floors, landings and treads.

402.3 Other spaces. All other spaces shall be provided with natural or artificial light sufficient to permit the maintenance of sanitary conditions, and the safe occupancy of the space and utilization of the appliances, equipment and fixtures.

SECTION 403 VENTILATION

403.1 Habitable spaces. Every habitable space shall have at least one openable window. The total openable area of the window in every room shall be equal to at least 45 percent of the minimum glazed area required in Section 402.1.

Exception: Where rooms and spaces without openings to the outdoors are ventilated through an adjoining room, the unobstructed opening to the adjoining room shall be at least 8 percent of the floor area of the interior room or space, but not less than 25 square feet (2.33 m²). The ventilation openings to the outdoors shall be based on a total floor area being ventilated.

403.2 Bathrooms and toilet rooms. Every bathroom and toilet room shall comply with the ventilation requirements for habitable spaces as required by Section 403.1, except that a window shall not be required in such spaces equipped with a mechanical ventilation system. Air exhausted by a mechanical ventilation system from a bathroom or toilet room shall discharge to the outdoors and shall not be recirculated.

403.3 Cooking facilities. Unless approved through the certificate of occupancy, cooking shall not be permitted in any rooming unit or dormitory unit, and a cooking facility or appliance shall not be permitted to be present in a rooming unit or dormitory unit.

Exception: Where specifically approved in writing by the code official.

403.4 Process ventilation. Where injurious, toxic, irritating or noxious fumes, gases, dusts, or mists are generated, a local exhaust ventilation system shall be provided to remove the contaminating agent at the source. Air shall be exhausted to the exterior and not be recirculated to any space.

403.5 Clothes dryer exhaust. Clothes dryer exhaust systems shall be independent of all other systems and shall be exhausted in accordance with the manufacturer's instructions.

**SECTION 404
OCCUPANCY LIMITATIONS**

404.1 Privacy. Dwelling units, hotel units, housekeeping units, rooming units, and dormitory units shall be arranged to provide privacy and be separate from other adjoining spaces.

404.2 Minimum room widths. A habitable room, other than a kitchen, shall not be less than 7 feet (2134 mm) in any plan dimension. Kitchens shall have a clear passageway of not less than 3 feet (914 mm) between counterfronts and appliances or counterfronts and walls.

404.3 Minimum ceiling heights. Habitable spaces, hallways, corridors, laundry areas, bathrooms, toilet rooms and habitable basement areas shall have a clear ceiling height of not less than 7 feet (2134 mm).

Exceptions:

1. In one and two family dwellings, beams or girders spaced not less than 4 feet (1219 mm) on center and projecting not more than 6 inches (152 mm) below the required ceiling height.

2. Basement rooms in one and two family dwellings occupied exclusively for laundry, study or recreation purposes, having a ceiling height of not less than 6 feet 8 inches (2033 mm) with not less than 6 feet 4 inches (1932 mm) of clear height under beams, girders, ducts and similar obstructions.

3. Rooms occupied exclusively for sleeping, study, or similar purposes and having a sloped ceiling over all or part of the room, with a clear ceiling height of at least 7 feet (2134 mm) over not less than one-third of the required minimum floor area. In calculating the floor area of such rooms, only those portions of the floor area with a clear ceiling height of 5 feet (1524 mm) or more shall be included.

404.4 Bedroom requirements. Every bedroom shall comply with the requirements of Sections 404.4.1 through 404.4.5.

404.4.1 Area for sleeping purposes. Every bedroom occupied by one person shall contain at least 70 square feet (6.5 m²) of floor area, and every bedroom occupied by more than one person shall contain at least 50 square feet (4.6 m²) of floor area for each occupant thereof.

404.4.2 Access from bedrooms. Bedrooms shall not constitute the only means of access to other bedrooms or habitable spaces and shall not serve as the only means of egress from other habitable spaces.

Exception: Units that contain fewer than two bedrooms.

404.4.3 Water closet accessibility. Every bedroom shall have access to at least one water closet and one lavatory without passing through another bedroom. Every bedroom in a dwelling unit shall have access to at least one water closet and lavatory located in the same story as the bedroom or an adjacent story.

404.4.4 Prohibited occupancy. Kitchens and nonhabitable spaces shall not be used for sleeping purposes.

404.4.5 Other requirements. Bedrooms shall comply with the applicable provisions of this code including, but not limited to, the light, ventilation, room area, ceiling height and room width requirements of this chapter; the plumbing facilities and water heating facilities requirements of Chapter 5; the heating facilities and electrical receptacle requirements of Chapter 6; and the smoke detector and emergency escape requirements of Chapter 7.

404.5 Overcrowding. Dwelling units shall not be occupied by more occupants than permitted by the minimum area requirements of Table 404.5.

**TABLE 404.5
MINIMUM AREA REQUIREMENTS**

SPACE	MINIMUM AREA IN SQUARE FEET		
	1-2 occupants	3-5 occupants	6 or more occupants
Living Room ^{a,b}	No requirements	120	150
Dining Room ^{a,b}	No requirements	80	100
Bedrooms	Shall comply with Section 404.4		

For SI: 1 square foot = 0.093 m²

a. See Section 404.5.2 for combined living/dining room spaces.

b. See Section 404.5.1 for limitations on determining the minimum occupancy area for sleeping purposes.

404.5.1 Sleeping area. The minimum occupancy area required by Table 404.5 shall not be included as a sleeping area in determining the minimum occupancy area for sleeping purposes. All sleeping areas shall comply with Section 404.4.

404.5.2 Combined spaces. Combined living room and dining room spaces shall comply with the requirements of Table 404.5 if the total area is equal to that required for separate rooms and if the space is located so as to function as a combination living room/dining room.

404.6 Efficiency unit. Nothing in this section shall prohibit an efficiency living unit from meeting the following requirements:

1. A unit occupied by not more than two occupants shall have a clear floor area of not less than 220 square feet (20.4 m²). A unit occupied by three occupants shall have a clear floor area of not less than 320 square feet (29.7 m²). These required areas shall be exclusive of the areas required by Items 2 and 3.
2. The unit shall be provided with a kitchen sink, cooking appliance, and refrigeration facilities, each having a clear working space of not less than 30 inches (762 mm) in front. Light and ventilation conforming to this code shall be provided.

3. The unit shall be provided with a separate bathroom containing a water closet, lavatory and bathtub or shower.

4. The maximum number of occupants shall be three.

404.7 Food preparation. All spaces to be occupied for food preparation purposes shall contain suitable space and equipment to store, prepare, and serve foods in a sanitary manner.

There shall be adequate facilities and services for the sanitary disposal of food wastes and refuse, including facilities for temporary storage.

CHAPTER 5

PLUMBING FACILITIES AND FIXTURE REQUIREMENTS

SECTION 501 GENERAL

501.1 Scope. The provisions of this chapter shall govern the minimum plumbing systems, facilities, and plumbing fixtures to be provided.

501.2 Responsibility. The owner of the structure shall provide and maintain such plumbing facilities and plumbing fixtures in compliance with these requirements. A person shall not occupy as owner-occupant or permit another person to occupy any structure or premise which does not comply with the requirements of this chapter.

SECTION 502 REQUIRED FACILITIES

502.1 Dwelling units. Every dwelling unit shall contain its own bathtub or shower, lavatory, water closet, and kitchen sink which shall be maintained in a sanitary, safe, working condition. The lavatory shall be placed in the same room as the water closet or located in close proximity to the door leading directly into the room in which such water closet is located. A kitchen sink shall not be used as a substitute for the required lavatory.

502.2 Rooming houses. At least one water closet, lavatory, and bathtub or shower shall be supplied for each four rooming units.

502.3 Hotels. Where private water closets, lavatories, and baths are not provided, one water closet, one lavatory, and one bathtub, or shower having access from a public hallway shall be provided for each ten occupants.

502.4 Employees' facilities. A minimum of one water closet, one lavatory and one drinking facility shall be available to employees.

502.4.1 Drinking facilities. Drinking facilities shall be a drinking fountain, water cooler, bottled water cooler, or disposable cups next to a sink or water dispenser. Drinking facilities shall not be located in toilet rooms or bathrooms.

SECTION 503 TOILET ROOMS

503.1 Privacy. Toilet rooms and bathrooms shall provide privacy and shall not constitute the only passageway to a hall, or other space, or to the exterior. A door and interior locking device shall be provided for all toilet rooms and bathrooms.

Exception: Common or shared public toilet rooms with more than one toilet shall not be lockable but shall be provided with privacy screening at each toilet facility

503.2 Location. Toilet rooms and bathrooms serving hotel units, rooming units, or dormitory units, or housekeeping units, shall have access by traversing not more than one flight of stairs and shall have access from a common hall or passageway.

503.3 Location of employee toilet facilities. Toilet facilities shall have access from within the employees' working area. The required toilet facilities shall be located not more than one story above or below the employees' working area and the path of travel to such facilities shall not exceed a distance of 500 feet (152 m). Employee facilities shall either be separate facilities or combined employee and public facilities.

Exception: Facilities that are required for employees in storage structures or kiosks, which are located in adjacent structures under the same ownership, lease, or control, shall not exceed a travel distance of 500 feet (152m) from the employees' regular working area to the facilities.

503.4 Floor surface. In other than dwelling units, every toilet room floor shall be maintained to be a smooth, hard, nonabsorbent surface to permit such floor to be easily kept in a clean and sanitary condition.

SECTION 504 PLUMBING SYSTEMS AND FIXTURES

504.1 General. All plumbing fixtures shall be properly installed and maintained in good working order, and shall be kept free from obstructions, leaks, and defects and be capable of performing the function for which such plumbing fixtures are designed. All plumbing fixtures shall be maintained in a safe, sanitary, and functional condition.

504.2 Fixture clearances. Plumbing fixtures shall have adequate clearances for usage and cleaning.

504.3 Plumbing system hazards. Where it is found that a plumbing system in a structure constitutes a hazard to the occupants or the structure, by reason of inadequate service, inadequate venting, cross connection, backsiphonage, improper installation, deterioration, or damage, or for similar reasons, the code official shall require the defects to be corrected to eliminate the hazard.

SECTION 505 WATER SYSTEM

505.1 General. Every sink, lavatory, bathtub, or shower, drinking fountain, water closet, or other plumbing fixture shall be properly connected to either a public water system or to an approved private water system.

All kitchen sinks, lavatories, laundry facilities, bathtubs, and showers shall be supplied with hot or tempered and cold running water in accordance with the *Georgia State Minimum Standard Plumbing Code*.

505.2 Contamination. The water supply shall be maintained free from contamination and all water inlets for plumbing fixtures shall be located above the flood-level rim of the fixture.

Shampoo basin faucets, janitor sink faucets, and other hose bibs, or faucets to which hoses are attached and left in place, shall be protected by an approved atmospheric type vacuum breaker or an approved permanently attached hose connection vacuum breaker.

505.3 Supply. The water supply system shall be installed and maintained to provide a supply of water to plumbing fixtures, devices and appurtenances in sufficient volume and at pressures adequate to enable the fixtures to function properly, safely, and free from defects and leaks.

505.4 Water heating facilities. Water heating facilities shall be properly installed, maintained, and capable of providing an adequate amount of water to be drawn at every required sink, lavatory, bathtub, shower, and laundry facility at a temperature of not less than 110°F (43°C).

A gas burning water heater shall not be located in any bathroom, toilet room, bedroom, or other occupied room normally kept closed, unless adequate combustion air is provided. An approved combination temperature and pressure relief valve and relief valve discharge pipe shall be properly installed and maintained on water heaters.

SECTION 506 SANITARY DRAINAGE SYSTEM

506.1 General. All plumbing fixtures shall be properly connected to either a public sewer system or to an approved private sewage disposal system.

506.2 Maintenance. Every plumbing stack, vent, waste and sewer line, fixture, fitting, appliance, and appurtenance shall function properly and be kept in good working order and in a sanitary condition free from obstructions, leaks, and defects.

SECTION 507 STORM DRAINAGE

507.1 General. Drainage of roofs and paved areas, yards and courts, and other open areas on the premises shall not be discharged in a manner that creates a public nuisance.

507.2 Flow control. Discharge from roofs, paved areas, yards and courts, and other areas on premises shall flow away from building foundations, shall not flow into sanitary sewers, and shall flow to a location approved by the city.

Yards and premises shall not be graded or shaped to direct undue storm water discharge upon adjacent land or property and shall not contain low areas where water may be trapped and induce insect breeding.

Storm water discharge piping systems shall be constructed and installed in accordance with Georgia State Minimum Standard Plumbing Code.

CHAPTER 6

MECHANICAL AND ELECTRICAL REQUIREMENTS

SECTION 601 GENERAL

601.1 Scope. The provisions of this chapter shall govern the minimum mechanical and electrical facilities and equipment to be provided in a structure intended to be occupied by humans.

601.2 Responsibility. The owner of the structure shall provide and maintain mechanical and electrical facilities and equipment in compliance with these requirements. A person shall not occupy as owner-occupant or permit another person to occupy any premises which does not comply with the requirements of this chapter.

SECTION 602 HEATING FACILITIES

602.1 Facilities required. Heating facilities shall be provided in structures as required by this section.

602.2 Residential occupancies. Dwellings shall be provided with heating facilities capable of maintaining a room temperature of 68°F (20°C) in all habitable rooms, bathrooms and toilet rooms based on the winter outdoor design temperature for the locality indicated in the *Georgia State Energy Code for Buildings (IECC)*.

Cooking appliances shall not be used to provide space heating to meet the requirements of this section. Such heating facilities shall be kept clean and in good working order.

602.3 Heat supply. Every owner and operator of any building who rents, leases, or lets one or more dwelling unit, rooming unit, dormitory, or guest room, on terms, either expressed or implied, to furnish heat to the occupants thereof shall supply heat during the period from 1 October through 30 April to maintain a temperature of not less than 68°F (20°C) in all habitable rooms, bathrooms and toilet rooms. Such heating facilities shall be kept clean and in good working order.

602.4 Occupiable work spaces. Indoor occupiable work spaces shall be supplied with heat during the period from 1 October through 30 April to maintain a temperature of not less than 65°F (18°C) during the period the spaces are occupied. Such heating facilities shall be kept clean and in good working order.

Exceptions:

1. Processing, storage and operation areas that require cooling or special temperature conditions.
2. Areas in which persons are primarily engaged in vigorous physical activities.

602.5 Room temperature measurement. The required room temperatures shall be measured 3 feet (914 mm) above the floor near the center of the room and 2 feet (610 mm) inward from the center of each exterior wall.

SECTION 603 MECHANICAL EQUIPMENT

603.1 Mechanical appliances. All mechanical appliances, fireplaces, solid fuel-burning appliances, cooking appliances, and water heating appliances shall be properly installed and maintained in a safe working condition, and shall be capable of performing the intended function.

603.2 Removal of combustion products. All fuel-burning equipment and appliances shall be connected to an approved chimney or vent in good working order.

Exception: Fuel burning equipment and appliances which are labeled for unvented operation.

603.3 Clearances. All required clearances to combustible materials shall be maintained in accordance to the appliance manufacturer's instructions.

Fuel fired appliances located in garages or other areas where motorized vehicles may be stored shall have their source of ignition elevated at least 18 inches above the floor.

Where subject to vehicle impact, all appliances shall be protected by an effective barrier sufficient to resist an impact force of 6,000 pounds at a point 36 inches above the floor.

603.4 Safety controls. All safety controls for fuel burning equipment shall be maintained in effective operation.

603.5 Combustion air. A supply of air for complete combustion of the fuel and for ventilation of the space containing the fuel burning equipment shall be provided for the fuel burning equipment.

603.6 Energy conservation devices. Devices intended to reduce fuel consumption by attachment to a fuel burning appliance, to the fuel supply line thereto, or to the vent outlet or vent piping therefrom, shall not be installed unless labeled for such purpose and the installation is specifically approved.

603.7 Duct systems. Duct systems shall be maintained free of obstructions and shall be capable of performing the required function.

All ductwork, grilles, registers, controls, and similar accessories of an appliance system shall be firmly secured in place and in good working order.

**SECTION 604
ELECTRICAL FACILITIES**

604.1 Facilities required. Every occupied building shall be provided with an electrical system in compliance with the requirements of this section and Section 605.

604.2 Service. The size and usage of appliances and equipment shall serve as a basis for determining the need for additional facilities in accordance with the *Georgia State Minimum Standard Electrical Code*.

Dwelling units shall be served by a three-wire, 120/240 volt, single phase electrical service and disconnecting means having a rating of not less than 100 amperes.

For all other installations, the service and disconnecting means shall have a rating of not less than 60 amperes.

604.3 Electrical system hazards. Where it is found that the electrical system in a structure constitutes a hazard to the occupants or the structure by reason of inadequate service, improper fusing, insufficient receptacle and lighting outlets, improper wiring or installation, deterioration or damage, or for similar reasons, the code official shall require the defects to be corrected to eliminate the hazard.

**SECTION 605
ELECTRICAL EQUIPMENT**

605.1 Installation. All electrical equipment, wiring and appliances, fixtures, devices, and appurtenances shall be properly installed and maintained in a safe and approved manner and shall be maintained in good working order.

605.2 Receptacles. Every habitable space in a dwelling shall contain at least two separate and remote receptacle outlets. Every laundry area shall contain at least one grounded-type receptacle or a receptacle with a ground fault circuit interrupter. Every bathroom shall contain at least one receptacle. Any new bathroom receptacle outlet shall have ground fault circuit interrupter protection.

605.3 Lighting fixtures. Every exterior entry door, public hall, interior stairway, toilet room, kitchen, bathroom, laundry room, furnace room, water heater room, garage, and basement shall contain at least one switched lighting fixture. Other rooms shall contain at least one switched lighting fixture or outlet for connecting portable lighting.

Exception: Existing chain-pull type lighting fixtures or automatically controlled motion sensor lighting fixtures, with a manual switching override, installed in rooms and other areas and in good working order may remain in place.

**SECTION 606
ELEVATORS, ESCALATORS AND DUMBWAITERS**

606.1 General. Elevators, dumbwaiters, and escalators shall be maintained to safely sustain all imposed loads, to operate properly, and to be free from physical defects and fire hazards. The most current certificate of inspection shall be on display at all times within the elevator, or attached to the escalator or dumbwaiter; or the certificate shall be available for public inspection in the office of the building operator.

606.2 Elevators. In buildings equipped with passenger elevators, at least one elevator shall be maintained in operation at all times when the building is occupied.

Exception: Buildings equipped with only one elevator shall be permitted to have the elevator temporarily out of service for testing or servicing.

CHAPTER 7

FIRE SAFETY REQUIREMENTS

SECTION 701 GENERAL

701.1 Scope. The provisions of this chapter, the *Georgia State Minimum Standard Fire Prevention Code*, and the *Life Safety Code* shall govern the minimum conditions and standards for fire safety relating to structures and exterior premises, including fire safety facilities and equipment and requirements for and maintenance of fire resistance rated construction to be provided.

701.2 Responsibility. The owner of the premises shall provide and maintain such fire safety facilities and equipment in compliance with these requirements. A person shall not occupy as owner-occupant or permit another person to occupy any premises that do not comply with the requirements of this chapter.

SECTION 702 MEANS OF EGRESS

702.1 General. A safe, continuous and unobstructed path of travel shall be provided from any point in a building or structure to the public way. Means of egress shall comply with the *Life Safety Code*.

702.2 Aisles. The required width of aisles in accordance with the *Georgia State Minimum Standard Fire Prevention Code* shall be unobstructed.

702.3 Locked doors. All means of egress doors shall be readily openable from the side from which egress is to be made without the need for keys, special knowledge or effort, except where the door hardware conforms to that permitted by the *Georgia State Minimum Standard Building Code*.

702.4 Emergency escape openings. Required emergency escape openings shall be maintained in accordance with the code in effect at the time of construction, and the following.

Required emergency escape and rescue openings shall be operational from the inside of the room without the use of keys or tools.

Bars, grilles, grates, or similar devices are permitted to be placed over emergency escape and rescue openings provided the minimum net clear opening size complies with the code that was in effect at the time of construction.

Such devices shall be releasable or removable from the inside without the use of a key, tool, or force greater than that which is required for normal operation of the escape and rescue opening.

SECTION 703 FIRE-RESISTANCE RATINGS

703.1 Fire-resistance-rated assemblies. The required fire resistance rating of fire resistance rated walls, fire stops, shaft enclosures, partitions, and floors shall be maintained.

703.2 Opening protectives. Required opening protectives shall be maintained in an operative condition. All fire and smokestop doors shall be maintained in operable condition. Fire doors and smoke barrier doors shall not be blocked or obstructed or otherwise made inoperable.

SECTION 704 FIRE PROTECTION SYSTEMS

704.1 General. All systems, devices and equipment to detect a fire, actuate an alarm, or suppress or control a fire, or any combination thereof, shall be maintained in an operable condition at all times in accordance with the *Georgia State Minimum Standard Fire Prevention Code*.

704.2 Smoke alarms. Single or multiple-station smoke alarms shall be installed and maintained in Groups R-2, R-3, R-4 and in dwellings not regulated in Group R occupancies, regardless of occupant load at all of the following locations:

1. On the ceiling or wall outside of each separate sleeping area in the immediate vicinity of bedrooms.
2. In each room used for sleeping purposes.
3. In each story within a dwelling unit, including basements and cellars but not including crawl spaces and uninhabitable attics. In dwellings or dwelling units with split levels and without an intervening door between the adjacent levels; a smoke alarm installed on the upper level shall suffice for the adjacent lower level provided that the lower level is less than one full story below the upper level.

Single or multiple-station smoke alarms shall be installed in other groups in accordance with the *Georgia State Minimum Standard Fire Prevention Code*.

704.3 Power source. In Group R occupancies and in dwellings not regulated as Group R occupancies, single station smoke alarms shall receive their primary power from the building wiring provided that such wiring is served from a commercial source and shall be equipped with a battery backup. Smoke alarms shall emit a signal when the batteries are low. Wiring shall be permanent

and without a disconnecting switch other than as required for overcurrent protection at the panel location.

Exception: Smoke alarms are permitted to be solely battery operated in buildings where no construction is taking place, buildings that are not served from a commercial power source, and in existing areas of buildings undergoing alterations or repairs that do not result in the removal of interior wall or ceiling finishes exposing the structure, unless there is an attic, crawl space, or basement available which could provide access for building wiring without the removal of interior finishes.

704.4 Interconnection. Where more than one smoke alarm is required to be installed within an individual dwelling unit in Group R-2, R-3, R-4 and in dwellings not regulated as Group R occupancies, the smoke alarms shall be interconnected in such a manner that the activation of one alarm will activate all of the alarms in the individual unit. The alarm shall be clearly audible in all bedrooms over background noise levels with all intervening doors closed.

Exceptions:

1. Interconnection is not required in buildings which are not undergoing alterations, repairs, or construction of any kind.
2. Smoke alarms in existing areas are not required to be interconnected where alterations or repairs do not result in the removal of interior wall or ceiling finishes exposing the structure, unless there is an attic, crawl space, or basement available which could provide access for interconnection without the removal of interior finishes.

CHAPTER 8

REFERENCED STANDARDS

Reference standards shall be those reference standards listed in the Georgia State Minimum Standard Codes for construction, the City of Peachtree Corners Zoning Code, and other laws and regulations particular to the use and systems addressed.

INDEX

A

ACCEPTED ENGINEERING METHODS..... 104.2

ACCESS

- Egress..... 702
- From bedrooms..... 404.4.2
- Plumbing fixtures, access for cleaning 504.2
- To public way..... 702.1
- Toilet room as passageway 503.1
- Water closet..... 404.4.3

ADJACENT

- Privacy (hotel units, rooming units)..... 404.1

ADMINISTRATION

- Scope..... 101.2

AGENT (See also OPERATOR; see OWNER) 202

- Registered Agent..... 312

AIR

- Combustion air..... 603.5

AISLES

- Minimum width..... 702.2

ALTERATION

- Applicability of other codes 102.3
- Condemnation Inspection 108.1, 108.2
- Inspection..... 104.3
- Prosecution 106.3
- Unlawful acts..... 106.1

ANCHOR

- Architectural trim 304.8
- Signs, marquees and awnings..... 304.9

APPEAL

- Application 111.1
- Board decision 111.2
- Code Enforcement Board 111.3
- Court review 111.7
- Hearing, emergency orders 109.6
- Notice of appeal 111.1
- Records..... 104.7
- Right to appeal..... 111.1
- Vote..... 111.2

APPLIANCE

- Cooking..... 403.3, 602.2
- Heating..... 602.2, 603.1
- Mechanical..... 603.1

APPLICATION

- Other codes 102.3

APPROVAL

- Alternatives 105.2

Authority 104.2, 105.2

Modifications 105.1

APPROVED

- Alternative materials, methods and equipment..... 105.2
- Definition 202
- Energy conservation devices 603.6
- Fireplaces..... 603.1
- Garbage storage facilities 307.3.1
- Modifications 105.1
- Used materials and equipment 105.4

ARCHITECTURAL

- Structural member..... 304.4
- Trim 304.8

ARTIFICIAL

- Lighting of habitable rooms 402.1
- Lighting of other spaces 402.3

AUTOMOBILE

- Motor vehicles 302.8

AWNING

- Signs, marquees and awnings 304.9

B

BALCONY

- Handrails and guardrails 306.1
- Maintenance..... 304.12, 305.5

BASEMENT

- Definition 202
- Hatchways..... 304.16
- Windows..... 304.17

BATHROOM

- Common bathrooms..... 502.3, 503.1
- Hotels 502.3
- Lighting..... 605.3
- Locks 503.1
- Outlets required..... 605.2
- Privacy..... 503.1
- Ventilation..... 403.2

BATHTUB

- Required facilities 502.1
- Rooming houses 502.2
- Sewage system 506.1
- Water heating facilities 505.4
- Water system 505.1

BOILER

- Unsafe equipment 108.1.2

C

CAPACITY

Heating facilities 602.2, 602.3, 602.4

CAR (See AUTOMOBILE)

CEILING

Basement rooms 404.3
Fire-resistance ratings 703.1
Interior surfaces 305.3
Minimum height 404.3

CHANGE, MODIFY

Application of other codes 102.3

CHIMNEY

Exterior structure 304.11
Fireplaces 603.1
Flue 603.2, 603.3

CLEANING

Access for cleaning 504.2
Bathroom and kitchen floors 305.3, 503.4
Disposal of garbage 307.3
Disposal of rubbish 307.3
Interior sanitation 307.1
Interior surfaces 305.3
Occupant 305.1
Plumbing facilities, maintained 504.1
Required plumbing facilities 502
Responsibility of persons 305.1
Trash containers 307.3.2
Vacant structures and land 301.3

CLEARANCE

Heating facilities 603.3
Plumbing fixtures 504.2

CLOSING

Streets 109.3
Vacant structures 108.2

CLOTHES DRYER

Exhaust 403.5

CODE OFFICIAL

Condemnation 108.1
Coordination of enforcement 104.8
Demolition 110
Duties 104
Emergency order 109
Enforcement authority 104
Failure to comply with demolition order 110.3
Identification 104.5
Inspections 104.3
Liability, relief of personal 103.5
Membership of board of appeals 111.2
Notice of violation 104.6, 107
Notices and orders 107
Official records 104.7

Personal liability 103.5
Placarding 108.4
Prosecution 106.3
Removal of placard 108.6
Right of entry 104.4
Rule-making authority 104.2
Transfer of ownership 107.5
Vacant structures 108.2
Voting of appeals board 111.2, 111.6

COLD WATER

Drinking 502.4
Required facilities 502
Rooming houses 502.2
Water system 505

COMBUSTION

Combustion air 603.5

CONDEMNATION

Closing of vacant structures 108.2
Failure to comply 110.3
General 108.1
Notices and orders 108.2, 108.3
Placarding 107.4
Removal of placard 108.6

CONFLICT

Conflict of interest 111.2.3
Coordination of inspections 104.8
Violations 106.1

CONNECTION

Plumbing fixtures 504.1
Sewage system 506.1
Water heating 505.4
Water system 505.1

CONSTRUCTION

Existing structures 101.2
Inactive 309

CONTAINER

Garbage 307.3.2
Rubbish storage 307.2.1

CONTINUOUS

Egress 702.1

CONTRACTOR

Conflict of interest 111.2.3

CONTROL

Insect and rat control 302.5, 304.5, 307.1
Safety controls 603.4

COOLING

Cooling towers 304.11

CORRIDOR

Accumulation of rubbish 307.1
Light 402.2
Lighting fixtures 605.3
Ratings maintained 703

Toilet rooms, access 503.1

Window and door frames 304.13

D

DAMP, DAMPNES

Roofs 304.7
Window, door frames 304.13

DANGEROUS, HAZARDOUS

Condemnation 108.1
Demolition 110
Electrical hazards 604.3
Elevators 606.1
Existing remedies 102.4
Fire safety 701.1
Heating facilities 602, 603.1
Imminent danger 202
Unsafe structures and equipment 108

DECKS

Handrails and guardrails 304.12
Maintenance 304.2, 304.10

DECORATION

Exterior structure 304.8

DEMOLITION

Existing remedies 102.4
Failure to comply 110.3
General 110
Notices & Orders 110.2
Salvage materials 110.4
Failure to comply 110.3

DETECTORS

Smoke 704.2

DETERIORATION

Exterior walls 304.6

DIRECT

Egress 702.1

DISPOSAL

Disposal of garbage 307.3
Disposal of rubbish 307.2

DOOR

Exit doors 702.3
Fire 703.2
Hardware 304.15
Insect screens 304.14
Interior surfaces 305.3
Locks 304.15, 702.3
Maintenance 304.13, 304.15
Weather tight 304.13

DORMITORY (ROOMING HOUSE, HOTEL, MOTEL)

Locked doors 702.3
Privacy 503.1, 503.2

DRAIN, DRAINAGE

Basement hatchways 304.16
Grading 302.2
Plumbing connections 506.1
Storm drainage 507

DUCT

Exhaust duct 304.9

DUST

Process ventilation 403.4

DWELLING

Cleanliness 305.1, 307.1
Definition 202
Electrical 604.1
Heating facilities 602
Required facilities 502
Space requirements 404.5

E

EASEMENT

Definition 202

EGRESS

Aisles 702.2
Common halls and stairways 402.2
Emergency escape 702.4
General 702.1
Lighting 402.2
Locked doors 702.3
Obstructions prohibited 702.1
Stairs, porches and railings 304.10, 305.5, 306.1

ELECTRIC, ELECTRICAL

Condemnation 108.1
Facilities required 604.1
Scope 601.1
Hazards 604.3
Installation 605.1
Lighting fixtures 605.3
Receptacles 604.3, 605.2
Responsibility 601.2
Service 604.2

ELEVATOR

Condemnation 108.1
General 606.1
Maintenance 606.1, 606.2

EMERGENCY	
Emergency measures	109
Emergency orders.....	109.1
Escape	702.4
ENFORCEMENT	
Coordination.....	104.8
Duties and powers	104
Scope	101.2
EQUIPMENT	
Alternative	105.2
Combustion air.....	603.5
Condemnation.....	108.1.2, 108.3
Electrical installation	605.1
Emergency order	109.1
Energy conservation devices	603.6
Fire safety requirements, responsibility	701.2
Flue	603.2
Installation	603.1
Interior structures.....	305.1
Placarding	108.3, 108.4
Prohibited use	108.5
Responsibility.....	601.2
Safety controls	603.4
Scope	101.2
Scope, mechanical and electrical	601.1
Unsafe.....	108
Used.....	105.4
EXCEPTION	
Rule-making authority.....	104.2
EXHAUST	
Clothes dryer.....	403.5
Exhaust ducts	304.9
Process ventilation.....	403.4
EXISTING	
Remedies	102.4
Scope	101.2
Structural members.....	304.4
Structures.....	101.3
EXTERIOR	
Decorative features.....	304.8
Egress.....	702.1
Exterior structure.....	304
Exterior walls and fences	304.6
Painting	304.2, 304.6
Rodent harborage	302.5, 303.5
Sanitation	302.1
Scope	301.1
Stair.....	304.10, 305.4, 306.1
Street numbers	304.3
Weather tight.....	304.13
EXTERMINATE	
Definition	202
Insect and rat control	302.5, 308.1

Responsibility of owner	301.2, 308.2
Responsibility of tenant-occupant	301.2, 308.3, 308.4, 308.5

F

FAN

Exhaust vents.....	302.6
--------------------	-------

FEES, EXPENSES, COST

Closing vacant structures.....	108.2
Demolition	110.1, 110.3, 110.4
Extermination	308.2, 308.3, 308.4, 308.5
General.....	103.5
Relief from personal liability	103.4
Responsibility, fire safety	701.2

FENCE

Accessory.....	302.7
Maintenance.....	304.2;304.6

FIRE

Fire-resistance ratings.....	703
General, fire-protection systems	704
Protection systems.....	704
Responsibility, fire safety	701.2
Scope	101.2
Scope, fire safety	701.1
Smoke detectors	704.1

FLAMMABLE LIQUID

Containers	108.1.2
------------------	---------

FLOOR, FLOORING

Area for sleeping purposes	404.5.1
Fire-resistance ratings.....	703.1
Interior surfaces.....	305.1, 305.3
Space requirements	404.5, 404.6

FOOD PREPARATION

Cooking equipment	403.3, 602.2
Sanitary condition.....	305.1, 404.7
Ventilation.....	304.14, 403.3

FOUNDATION

Condemnation	108.1.1
Foundation walls	304.5
Window and door frames	304.13

G

GAS

Energy conservation devices	603.6
Exhaust vents.....	302.6
Process ventilation	403.4

GLAZING	
Materials	304.13.1
GRADE	
Drainage	302.2, 507
GUARD	
Basement windows	304.17
Definition	202
Handrails	304.12

H

HABITABLE	
Definition	202
Light	402
Minimum ceiling height	404.3
Minimum room width	404.2
Nonresidential heating facilities	602.4
Prohibited use	404.4.4
Required plumbing facilities	502
Residential heating facilities	602.2, 602.3
Space requirements	404.5
Ventilation	403
HANDRAIL	
Handrails	304.12, 305.5, 306.1
Stairs and porches	304.10
HARDWARE	
Door hardware	304.15, 702.3
Openable windows	304.13.2
HAZARDOUS (See DANGEROUS, HAZARDOUS)	
HEAT, HEATING	
Bathtub or shower	505.4
Cooking equipment	403.3, 602.2
Energy conservation devices	603.6
Fireplaces	603.1
Heating	603.1
Kitchen sink	505.4
Mechanical equipment	603.1
Required capabilities	602
Residential heating	602.2, 602.3
Scope	101.2
Supply	602.3
Water heating	505.4
Water system	505
HOUSEKEEPING UNIT	
Definition	202
HEIGHT	
Minimum ceiling height	404.3
HOT (See HEAT, HEATING)	

HOTELS, ROOMING HOUSES AND DORMITORY UNITS, MOTELS	
Definition	202
Locked doors	702.3
Privacy	503.1
Toilet rooms	503

I

IDENTIFICATION	
Code official	104.5
INACTIVE CONSTRUCTION SITES	309
INFESTATION	
Condemnation	108.1.3
Definition	202
Insect and rat	302.5, 304.14, 307.1, 308.1
INSECTS	
Extermination	308
Garbage storage facilities	307.3.1
Infestation	308.1
Insect screens	304.14
INSPECTIONS	
Coordination	104.8
General	104.3
Right of entry	104.4
INSPECTOR	
Coordination of inspections	104.8
Identification	104.5
Inspections	104.3
Official records	104.7
INTENT	
Code	101.3
Rule-making authority	104.2
INTERIOR	
Interior structure	305
Interior surfaces	305.3
Means of egress	702
Sanitation	305.1

J

JUNK CAR (see Motor Vehicle)	302.8
JURISDICTION	
Title	101.1

K

KITCHEN	
Electrical outlets required	605.2
Kitchen sink	502.1

Minimum width	404.2
Prohibited use	404.4.4
Water heating facilities.....	505.4

L

LANDING

Handrails and guards	304.12, 305.4, 305.5, 306.1
-------------------------------	-----------------------------

LAUNDRY

Room lighting	605.3
Water heating facilities.....	505.4

LAVATORY

Hotels	502.3
Required facilities.....	502
Rooming houses	502.2
Sewage system.....	506
Water heating facilities.....	505.4
Water system	505

LEASE (SELL, RENT)

Heat supplied	602.3
Salvage materials	110.4
Transfer of ownership	107.5

LIEN

Closing of vacant structures	108.2
Demolition	110.3
Failure to comply.....	110.3

LIGHT, LIGHTING

Common halls and stairways	402.2, 605.3
Fixtures	605.3
General	402
Habitable rooms.....	402.1
Other spaces.....	402.3
Responsibility.....	401.2
Scope.....	101.2
Spaces or rooms.....	402.1
Toilet rooms	605.3

LIVING ROOM

Minimum occupancy area requirements.....	404.5
--	-------

LOAD, LOADING

Elevators, escalators and dumbwaiters	606.1
Handrails	304.12
Live load.....	304.4, 305.2
Stairs and porches	304.10, 305.4
Structural members.....	304.4, 305.2

M

MAINTENANCE

Required	102.2
----------------	-------

MATERIAL

Alternative	105.2
Clearances, heating facilities	603.3
Salvage	110.4
Used	105.4

MEANS OF EGRESS (See EGRESS)

MECHANICAL

Garbage facilities	307.3.1
Installation	603.1
Responsibility	601.2
Scope	601.1
Ventilation, general	403
Ventilation, toilet rooms.....	403.2

MINIMUM

Ceiling height.....	404.3
Occupancy area requirements	404.5
Room width	404.2
Scope	301.1

MODIFICATION

Approval	105.1
----------------	-------

MOTEL (See HOTELS)

MOTOR VEHICLES

Inoperative.....	302.8
Painting	302.8

N

NATURAL

Lighting.....	401.3, 402
Ventilation.....	401.3, 403

NOTICE

Appeal	111.1
Form	107.2
Method of service	107.3
Orders	107
Owner, responsible person	107.1
Penalties.....	107.4
Placarding of structure	108.4
Transfer of ownership	107.5
Vacating structure	108.2

NOXIOUS

Process ventilation	403.4
Weeds	302.4

NUISANCE

Closing of vacant structures.....	108.2
-----------------------------------	-------

O

OBSTRUCTION

Light.....	402.1
Right of entry	104.4

OCCUPANCY (See USE)	
OPEN	
Habitable rooms.....	403.1
Locked doors	702.3
OPEN OR OUTDOOR STORAGE.....	310
OPENABLE	
Definition	202
Locked doors	702.3
Windows	304.12.2
OPERATOR	
Definition	202
ORDER (See NOTICE)	
ORDINANCE, RULE	
Applicability	102
Application for appeal	111.1
OUTLET	
Electrical	605.2
OWNER	
Closing of vacant structures	108.2
Definition	202
Demolition	110
Extermination	308.2
Failure to comply.....	110.3
Insect and rat control	302.5, 308.2, 308.4
Notice.....	107.1, 108.3
Placarding of structure.....	108.4
Responsibility.....	301.2
Responsibility, fire safety	701.2
Responsibility, light, ventilation.....	401.2
Responsibility, mechanical and electrical	601.2
Responsibility, plumbing facilities	501.2
Right of entry.....	104.4
Rubbish storage.....	307.2.1
Scope.....	101.2
Transfer of ownership	107.5

P

PARKING (VEHICLES).....	302.8(B)
PASSAGEWAY	
Common hall and stairway	402.2
Interior surfaces	305.3
Toilet rooms, direct access	503.1
PENALTY	
Notices and orders.....	107.4
Placarding of structure.....	108.4
Prohibited use.....	108.5
Removal of placard.....	108.6
Scope.....	102.2

Violations.....	106.4
PEST (VERMIN)	
Condemnation.....	108.1
Extermination	308.1
Insect and rat control.....	302.5, 304.14, 308.1
PLACARD, POST	
Closing	108.2
Condemnation	108.1
Demolition	110
Emergency, notice	109.1
Notice to owner	107.1, 108.3
Placarding of structure	108.4
Prohibited use	108.5
Removal	108.6
PLUMBING	
Access.....	504.2
Clean and sanitary	504.1
Connections	505.1
Contamination	505.2
Employee's facilities	503.3
Fixtures.....	504.1
Required facilities.....	502
Responsibility	501.2
Sanitary drainage system.....	506
Scope	501.1
Storm drainage.....	507
Supply	505.3
PORCH	
Handrails	306.1
Structurally sound	304.10
PORTABLE (TEMPORARY)	
Cooking equipment	603.1
PRESSURE	
Water supply	505.3
PRIVATE, PRIVACY	
Bathtub or shower	503.1
Occupancy limitations	404.1
Required plumbing facilities	502
Sewage system.....	506.1
Water closet and lavatory.....	502.3, 503.1
Water system	505.1
PROPERTY, PREMISES	
Access to public way.....	702.1
Cleanliness.....	304.1, 307.1
Condemnation	108
Definition	202
Demolition	110
Emergency measures	109
Exterior areas	302
Extermination, multiple occupancy	302.5, 308.4
Extermination, single occupancy.....	302.5, 308.3
Failure to comply.....	110.3
Grading and drainage	302.2
Responsibility	301.2

Scope	301.1
Storm drainage	507
Vacant structures and land	301.3
PROTECTION	
Basement windows	304.17
Fire-protection systems	704
Signs, marquees and awnings.....	304.9
PUBLIC	
Access to public way	702.1
Cleanliness	304.1, 305.1
Egress	702.1
Hallway	502.3
Sewage system.....	506.1
Toilet rooms	503
Vacant structures and land	301.3
Water system	505
PUBLIC WAY	
Definition	202

R

RAIN	
Basement hatchways.....	304.16
Exterior walls.....	304.6
Grading and drainage	302.2
Roofs.....	304.7
Window and door frames.....	304.13
RATS	
Basement hatchways.....	304.16
Condemnation.....	108
Exterior surfaces.....	304.5
Extermination	302.5, 308
Guards for basement windows	304.17
Harborage	302.5
Insect and rat control	308.1
RECORD	
Official records	104.7
REHABILITATION	
Intent	101.3
REPAIR	
Application of other codes	102.3
Chimneys	304.11
Demolition	110.1
Exterior surfaces.....	304.1
Maintenance	102.2
Public areas	302.3
Signs, marquees and awnings.....	304.9
Stairs and porches	304.10
Weather tight.....	304.13
Workmanship	102.5
REPORTS	
Test reports.....	105.3.2

RESIDENTIAL	
Extermination	308
Residential heating.....	602.2
Scope	101.2

RESPONSIBILITY	
Extermination	308
Fire safety.....	701.2
Garbage disposal	307.3
General.....	301.2
Mechanical and electrical.....	601.2
Persons	301.1
Placarding of structure	108.4
Plumbing facilities	501.2
Rubbish storage	307.2.1
Scope	101.2,301.1

REVOKE, REMOVE	
Demolition	110
Existing remedies.....	102.4
Process ventilation	403.4
Removal of placard	108.6
Rubbish removal	307.2.1

RIGHT OF ENTRY	
Duties and powers of code official	104.4
Inspections	104.3

ROOF	
Exterior structure	304.1
Roofs	304.6
Storm drainage.....	507

ROOM	
Cooking facilities	403.3
Direct access.....	503.2
Habitable	402.1
Heating facilities	602
Light.....	402
Minimum ceiling heights.....	404.3
Minimum occupancy area requirements	404.5
Minimum width	404.2
Overcrowding	404.5
Prohibited use	404.4.4
Separation	404.5.2
Sleeping	404.4
Temperature.....	602.5
Toilet.....	503
Ventilation.....	403

ROOMING HOUSES (See DORMITORY)

RUBBISH	
Accumulation.....	307.1
Definition	202
Disposal.....	307.2
Garbage facilities	307.3.1
Rubbish storage	307.2.1
Storage.....	307.2.1

S

SAFETY, SAFE

Chimney	304.11
Condemnation.....	108.1
Electrical installation	605.1
Emergency measures	109
Fire safety requirements	701
Fireplaces	603.1
Intent	101.3
Safety controls	603.4
Scope.....	101.2
Unsafe structures and equipment.....	108

SANITARY

Bathroom and kitchen floors	305.3
Cleanliness	304.1, 305.1
Disposal of garbage	307.3
Disposal of rubbish	307.2
Exterior property areas	302.1
Exterior structure.....	304.1
Food preparation.....	404.7
Furnished by occupant	302.1
Interior surfaces	304.3
Plumbing fixtures	504.1
Required plumbing facilities	502
Sanitation	305.1, 305.3
Scope.....	101.2

SASH

Window	304.13
--------------	--------

SCREENS

Insect screens.....	304.14
---------------------	--------

SECURITY

Basement hatchways.....	304.18.3
Building	304.18
Doors	304.18.1
Vacant structures and land	301.3
Windows	304.18.2

SELF-CLOSING SCREEN DOORS

Insect screens.....	304.14
---------------------	--------

SEPARATION

Fire-resistance ratings	703
Privacy	404.1
Separation of units	404.1
Water closet and lavatory	502.1

SERVICE

Electrical	604.2
Method	107.3
Notices and orders.....	107.1, 108.3
Service on occupant	108.3

SEWER

General	506.1
Maintenance	506.2

SHOWER

Bathtub or shower	502.1
Rooming houses	502.2
Water heating facilities	505.4
Water system	505

SIGN

Signs, marquees and awnings	304.9
-----------------------------------	-------

SINGLE-FAMILY DWELLING

Extermination	308
---------------------	-----

SINK

Kitchen sink.....	502.1
Sewage system.....	506
Water supply	505.3

SIZE

Habitable room, light	402
Habitable room, ventilation.....	403
Room area.....	Table 404.5

SLEEPING

Area for sleeping purposes	404.4.1
Cooking facilities	403.3

SMOKE

Alarms	704.2
Detectors	704.1
Interconnection.....	704.4
Power source	704.3

SPACE

General, light.....	402
General, ventilation	403
Occupancy limitations	404
Privacy.....	404.1
Scope	401.1

STACK

Chimneys	304.11
----------------	--------

STAIRS

Common halls and stairways, light	402.2
Exit facilities.....	305.4, 305.5
Handrails	304.12, 305.5
Lighting.....	605.3
Public areas.....	302.3
Stairs and porches	304.10

STANDARD

Referenced.....	102.7
-----------------	-------

STORAGE

Food preparation.....	404.7
Garbage storage facilities	307.3
Rubbish storage facilities	307.2.1
Sanitation	307.1

STRUCTURE

Accessory structures	302.7
Burned.....	313
Closing of vacant structures.....	108.2
Definition	202

Emergency measures	109
General, exterior	304.1
General, condemnation	108.1
General, interior structure	305.1
Placarding of structure	108.4
Scope	301.1
Structural members.....	304.4, 305.2
Vacant structures and land	301.3

SUPPLY

Combustion air.....	603.5
Connections	505.1
Water heating facilities.....	505.4
Water supply	505.3
Water system	505

SURFACE

Exterior surfaces	304.2, 304.6
Interior surfaces	305.3

SWIMMING

Swimming pools.....	303.1, 303.2
---------------------	--------------

T

TEMPERATURE

Nonresidential structures	602.4
Residential buildings	602.2
Water heating facilities.....	505.4

TENANT

Scope	101.2
-------------	-------

TEST, TESTING

Agency	105.3.2
..... Required	105.3

TOXIC

Process ventilation.....	403.4
--------------------------	-------

TRASH

Rubbish and garbage	307
---------------------------	-----

TREAD

Stair.....	304.10, 305.4
------------	---------------

TREES.....	311
-------------------	------------

U

UNOBSTRUCTED

Access to public way	702.1
General, egress	702.1

UNSAFE

Equipment.....	108.1.2
Existing remedies.....	102.4
General, condemnation	108, 110
General, demolition.....	110

Notices and orders	107, 108.3
Structure.....	108.1.1

USE

Application of other codes.....	102.3
General, demolition	110

V

VACANT

Closing of vacant structures.....	108.2
Emergency measure	109
Method of service.....	107.3, 108.3
Notice to owner or to person responsible	107, 108.3
Placarding of structure	108.4
Vacant structures and land	301.3

VAPOR

Exhaust vents.....	302.6
Process ventilation	403.4

VEHICLES

Inoperative.....	302.8
Painting	302.8

VENT

Connections	504.3
Exhaust vents.....	302.6
Flue	603.2

VENTILATION

Clothes dryer exhaust	403.5
Combustion air	603.5
Definition	202
General, ventilation	403
Habitable rooms	403.1
Process ventilation	403.4
Recirculation.....	403.2, 403.4
Toilet rooms.....	403.2

VERMIN

Condemnation.....	108.1.3
Insect and rat control.....	302.5, 308

VIOLATION

Condemnation	108
General.....	106
Notice	107, 108.3
Penalty	106.4
Placarding of structure	108.4
Prosecution	106.3
Strict liability offense	106.3, 202
Transfer of ownership	107.5

W

WALK

Sidewalks	302.3
-----------------	-------

	Ventilation.....	403
	Weather tight.....	304.13
	Window and door frames	304.13
WALL		
	Accessory structures.....	302.7
	Exterior surfaces.....	304.2, 304.6
	Exterior walls.....	304.6
	Foundation walls.....	304.5
	General, fire-resistance rating	703.1
	Interior surfaces.....	305.3
	Outlets required	605.2
	Temperature measurement	602.5
WASTE		
	Disposal of garbage.....	307.3
	Disposal of rubbish	307.2
	Dwelling units.....	502.1
	Garbage storage facilities	307.3.1
WATER		
	Basement hatchways.....	304.16
	Connections	506.1
	Contamination.....	505.2
	General, sewage.....	506
	General, storm drainage	507
	General, water system.....	505
	Heating.....	505.4
	Hotels.....	502.3
	Kitchen sink.....	502.1
	Required facilities.....	502
	Rooming houses	502.2
	Supply	505.3
	System	505
	Toilet rooms	503
	Water heating facilities.....	505.4
WEATHER, CLIMATE		
	Heating facilities.....	602
	Rule-making authority.....	104.2
WEATHERSTRIP		
	Window and door frames.....	304.13
WEEDS		
	Noxious weeds.....	202; 302.4
WIDTH		
	Minimum room width.....	404.2
WIND		
	Weather tight.....	304.13
	Window and door frames.....	304.13
WINDOW		
	Emergency escape	702.4
	Glazing.....	304.13.1
	Guards for basement windows	304.17
	Habitable rooms.....	402.1
	Insect screens.....	304.14
	Interior surface.....	305.3
	Light	402
	Openable windows.....	304.13.2
	Toilet rooms	403.2